


INDUSTRIAL COMPONENT DATA

2CSR772140R3204 ABB I.com.DS202CRM 2p C 20A A 10kA 300mA

Brand: ABB | Manufacturer Part Number: 2CSR772140R3204



Manufacturer	ABB
MPN / Reference	2CSR772140R3204
Catalog number	772140
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-27E1DA2D37
Generated	2026-08-04

Product Overview

I.com.DS202CRM 2p C 20A A 10kA 300mA

Residual Current Circuit Breaker with Overcurrent Protection DS202CR M - 2P - 300 mA - 20 A - C - Type A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A9845

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 76.95 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108469A0544

Environmental Product Declaration - EPD 9AKK108467A5738

Technical

Type of Residual Current Type A

Test Voltage (Ut) Minimum 117 V

Maximum 254 V

Rated Ultimate Short-Circuit Breaking Capacity (Icu) 10 kA

Rated Service Short-Circuit Breaking Capacity (Ics) 7.5 kA

Maximum Surge Current 0.25 kA

Power Supply Connection Arbitrary

Energy Limiting Class 3

Electrical Endurance 10000 operations

Mechanical Endurance 20000 operations

Number of Protected Poles 2

Number of Poles 2P

Fault Indication Blue Flag on Window

Operating Characteristic Instantaneous

Position of Neutral Terminals Right

Left

Tightening Torque 4 N·m

Accessory Type Auxiliary contact

Signal contact / auxiliary contact

Earthing Switch Type Undelayed

Accessories Available Yes

Number of Batteries 0

Connecting Capacity Busbar 10...10 mm²

Flexible 1...25 mm²

Rigid Solid 1...35 mm²

Rated Cross-Section 1 - Solid-Core 1 ... 35 mm²

4 - Multi-Wired 1 ... 25 mm²

Wire Stripping Length 11 mm

Electrical

Tripping Characteristic C

Rated Operational Voltage acc. to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSR772140R3204 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.