

INDUSTRIAL COMPONENT DATA

2TLA020006R2201 ABB P.Superior LED N Anti-Tamping Tape

Brand: ABB | Manufacturer Part Number: 2TLA020006R2201



Manufacturer	ABB
MPN / Reference	2TLA020006R2201
Catalog number	020006
Category	Agreement switch
Minimum order	1 Pcs
Document ID	EO-F37D709C41
Generated	2026-08-01

Product Overview

P.Superior LED N Anti-Tamping Tape
 JSJD4-2 Black Three-position handheld device - Top part

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Fences and rolling doors**

Additional Product Information

Ordering
 Minimum Order Quantity 1 piece
 Customs Tariff Number 8536909599
 Product Main Type JSJD4
 Product Name Three-position handheld device - Top part
 Sub-Function 1 front and 1 top auxiliary buttons
 Sub-Function 2 Holder for Eva (home position) with bottom part AL
 Anti-tamper available as option (not with AK bottom)
 Status Indicator Yes
 Popular Downloads
 Data Sheet, Technical Information 2TLC010001C0202
 CAD Dimensional Drawing 2CDC001079B0201
 Marketing Video 2TLC010018N0201
 Installation
 Wiring Diagram 2TLC010143D0201

Dimensions

Product Net Depth / Length 340 mm

Product Net Height 157 mm

Product Net Width 56 mm

Product Net Weight 0.139 kg

CAD Dimensional Drawing 2CDC001079B0201

Safety Information

Performance Level (PL) Up to e

B10d Value Operations to Bottom Position 968 000

Operations to Middle Position 2 million

Technical**Communication Interface Contacts**

Connection Configuration Depends on bottom part

Maximum Switching Current Main Circuit 0.02 mA

Maximum Switching Voltage Main Circuit 30 V

Minimum Switching Capacity Main Circuit 8 mA, 10 VDC

Number of Contacts CO 2

Number of Contacts NC 0

Number of Contacts NO 0

Rated Operational Current DC-12 (Ie) (24 V) 0.02 A

Rated Operational Voltage 24 V DC

Technical Information Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2TLA020006R2201 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.