

INDUSTRIAL COMPONENT DATA

2TLA920502R0003 ABB HD5-B-101 3-position knob

Brand: ABB | Manufacturer Part Number: 2TLA920502R0003



Manufacturer	ABB
MPN / Reference	2TLA920502R0003
Catalog number	920502
Category	Agreement switch
Minimum order	1 Pcs
Document ID	EO-2C5B95860F
Generated	2026-07-27

Product Overview

HD5-B-101 3-position knob

HD5-B-101 3-position controller

Three position device with AS-i Integrated technology. With Emergency stop button & 1 front + 2 top auxiliary buttons. Home position sensor and flashlight. M12-5 male connector. HD5 is suitable for Food and Beverage applications with the following features: Resistant to most chemicals, fiberglass reinforced plastic, anti-condensation membrane, IP65.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Fences and rolling doors

Additional Product Information

b'

General Information

Extended Product Type: HD5-B-101 Product ID: 2TLA920502R0003 EAN: 4013614554018 Catalog Description: HD5-B-101 Three-position device AS-i Long Description: Three position device with AS-i Integrated technology. With Emergency stop button & 1 front + 2 top auxiliary buttons. Home position sensor and flashlight. M12-5 male connector. HD5 is suitable for Food and Beverage applications with the following features: Resistant to most chemicals, fiberglass reinforced plastic, anti-condensation membrane, IP65.

Additional Information

Product Name: Three-position handheld device - Complete Function: Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area. Developed for the Food and Beverage industry. Sub-Function: 1 front and 2 top auxiliary buttons Sub-Function 2: Flashlight

Home position sensor Special Functions: Emergency Stop Button Status Indicator: Yes Application: Suitable for Food and Beverage Safety Information

Certification Agency:TÜV, cULusPerformance Level (PL):Up to eB10d Value:2 million operations to middle position
968 000 operations to bottom positionTechnical
Communication Interface:AS-iConnection Configuration:M12-5 maleNumber of Contacts CO:2Number of Contacts
NC:0Number of Contacts NO:0Rated Operational Current DC-12 (Ie):(24 V) 0.02 AEnvironmental
Degree of Protection:IP65Technical UL/CSA
Enclosure Type UL/CSA:1Popular Downloads
Data Sheet, Technical Information:\n2TLC010093L0201Instructions and Manuals:\n2C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2TLA920502R0003 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.