

INDUSTRIAL COMPONENT DATA

3AXD50000047765 ACS480-04-02A7-4 ABB ACS480-04-02A7-4 PN: 0.75 kW, IN: 2.6 A

Brand: ABB | Manufacturer Part Number: ACS480-04-02A7-4



Manufacturer	ABB
MPN / Reference	ACS480-04-02A7-4
Catalog number	ACS480-04-02A7-4
Category	Motor drives
Minimum order	1 unit
Document ID	EO-22AE16D9D3
Generated	2026-08-04

Product Overview

3AXD50000047765 ACS480-04-02A7-4 ABB ACS480-04-02A7-4 PN: 0.75 kW, IN: 2.6 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Motor drives > General range

Additional Product Information

Features Type code ACS480-04-02A7-4

Voltage 380-480 V

Heavy-duty output power (PHd) 0,55

Heavy-duty output current (IHd) 1,8

Maximum output current (Imax) 3,2

Light-overload output power (PLd) 0,75

Light-overload output current (ILd) 2,5

Nominal output power (PN) 0,75

Rated current (IN) 2,6

Dimensions (HxWxD) 223x73x208 mm

Net Weight 1.7 kg

Standard Features Cabinet mounted general purpose drive

IP20

Assistant control panel with USB-port (ACS-AP-S)

Entry from bottom

Safe torque off (STO), SIL 3 PL e

Braking chopper

Coated boards

Quick guides with default set of languages (quick installation and start up, safety manual)

Fixed I/O connections: 2xDI, 1xRO, 1xSTO

I/O module with Modbus RTU with additional I/O connections: 4 x DI, 2 x AI, 2 x AO, 2 x RO

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / ACS480-04-02A7-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.