

## INDUSTRIAL COMPONENT DATA

**AF12-30-22-41 1SBL157001R4122 ABB AF12-30-22-41  
24-60V50/60HZ Contactor**

Brand: ABB | Manufacturer Part Number: AF12-30-22-41



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | AF12-30-22-41                 |
| Catalog number  | 1SBL157001R4122               |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-BFAD484A1A                 |
| Generated       | 2026-08-04                    |

**Product Overview**

AF12-30-22-41 24-60V50/60HZ Contactor  
AF12-30-22-41 CONT. 3P BOB 24-60VAC

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path      ABB > Contactors and overload relays > AF contactors to 38 A

**Additional Product Information**

AF12 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage  $U_c \min. \dots U_c \max.$  Only four coils cover control voltages between 24...500 V 50/60 Hz. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 2-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles with a non-removable front-mounted 2 N.O. + 2 N.C. auxiliary contact block, side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 including the "Mechanically Linked" symbol on the contactor side. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC operated - Accessories: a wide range of accessories is available. Note: 2-stack contactors available in some countries: please consult your ABB representative.

Ordering

EAN:3471523110502

Minimum Order Quantity:1 piece

Customs Tariff Number:85369085

Dimensions

Product Net Width:45mm

Product Net Depth:110.5mm

Product Net Height:86mm

Product Net Weight:0.320kg

Container Information

Package Level 1 Units:1 piece

Packag...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / AF12-30-22-41 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.