

INDUSTRIAL COMPONENT DATA

1SBL176561R2100 ABB AF16ZB-22-00-21 24-60V50/60HZ 20-60VDC Contactor

Brand: ABB | Manufacturer Part Number: 1SBL176561R2100



Manufacturer	ABB
MPN / Reference	1SBL176561R2100
Catalog number	176561
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-06E04296A0
Generated	2026-08-05

Product Overview

AF16ZB-22-00-21 24-60V50/60HZ 20-60VDC Contactor

AF16ZB-22-00CONT.TR. B.24-60VAC20-60VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > AF contactors to 38 A

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC100220C0201

Instructions and Manuals 1SBC101027M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 45 mm

Product Net Depth / Length 77 mm

Product Net Height 86 mm

Product Net Weight 0.31 kg

Technical

Number of Main Contacts NO 2

Number of Main Contacts NC 2

Number of Auxiliary Contacts NO 0

Number of Auxiliary Contacts NC 0

Number of Poles 4P

Standards IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.

Rated Operational Voltage Main Circuit 690 V

Rated Frequency (f) Control Circuit 50 / 60 Hz

Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 35 A

Rated Operational Current AC-1 (I_e) (690 V) 40 °C 30 A

(690 V) 60 °C 30 A

(690 V) 70 °C 26 A

Rated Operational Current AC-3 (I_e) (415 V) 60 °C 18 A

(440 V) 60 °C 18 A

(500 V) 60 °C 15 A

(690 V) 60 °C 10.5 A

(380 / 400 V) 60 °C 18 A

(220 / 230 / 240 V) 60 °C 18 A

Rated Operational Power AC-3 (P_e) (400 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL176561R2100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.