

INDUSTRIAL COMPONENT DATA

1SFL527002R1400 ABB AF205-30-00-14 Contactor

Brand: ABB | Manufacturer Part Number: 1SFL527002R1400



Manufacturer	ABB
MPN / Reference	1SFL527002R1400
Catalog number	527002
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A0CA5E4D76
Generated	2026-08-02

Product Overview

AF205-30-00-14 Contactor

AF205-30-00-14 CONT. 3P B. 250-500VAC-DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > AF contactors 100A to 370A

Additional Product Information

A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V. Operated with wide control voltage range 250-500 V, 50/60 Hz and DC

Ordering

EAN:7320500480533

Minimum Order Quantity:1 piece

Customs Tariff Number:85364900

Dimensions

Product Net Width:105.0mm

Product Net Depth:152.0mm

Product Net Height:196.0mm

Product Net Weight:2.740kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:200 mm

Package Level 1 Length:220 mm

Package Level 1 Height:280 mm

Package Level 1 Gross Weight:3.19 kg

Package Level 1 EAN:7320500480533

Technical

Number of Main Contacts NO:3

Number of Main Contacts NC:0

Number of Auxiliary Contacts NO:0

Number of Auxiliary Contacts NC:0

Rated Operational Voltage:Main Circuit 1000 V

Rated Frequency (f):Main Circuit 50/60 Hz

Conventional Free-air Thermal Current (I_{th}):acc. to IEC 60947-4-1, Open Contactors q = 40 °C 350 A

Rated Operational Current AC-1 (I_e):(690 V) 55 °C 300 A

(690 V) 40 °C 350 A

(1000 V) 40 °C 275 A

(1000 V) 55 °C 250 A

(690 V) 70 °C 240 A

(1000 V) 70 °C 200 A

Rated Operational Current AC-3 (I_e):(1000 V) 55 °C 100 A

(690 V) 55 °C 165 A

(220 / 230 / 240 V) 55 °C 205 A

(415 V) 55 °C 205 A

(440 V) 55 °C 205 A

(380 / 400 V) 55 °C 205 A

(500 V) 55 °C 165 A

Rated Operational Power AC-3 (P_e):(500 V) 110 kW

(1000 V) 132 kW

(690 V) 160 kW

(220 / 230 / 240 V) 55 kW

(380 / 400 V) 110 kW

(440 V) 132 kW

(415 V) 110 kW

Rated Breaking Capacity AC-3 acc. t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFL527002R1400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.