

INDUSTRIAL COMPONENT DATA

AF26-30-00-41 1SBL237001R4100 ABB AF26-30-00-41 24-60V50/60HZ Contactor

Brand: ABB | Manufacturer Part Number: AF26-30-00-41



Manufacturer	ABB
MPN / Reference	AF26-30-00-41
Catalog number	1SBL237001R4100
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-238D356E04
Generated	2026-08-03

Product Overview

AF26-30-00-41 24-60V50/60HZ Contactor

AF26-30-00-41 CONT. 3P BOB 24-60VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > AF contactors to 38 A

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

EPLAN Data 9AAC159659_EPLAN

Instructions and Manuals 1SBC101027M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

Dimensions

Product Net Width 45 mm

Product Net Depth / Length 86 mm

Product Net Height 86 mm

Product Net Weight 0.31 kg

Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0
Number of Auxiliary Contacts NO 0
Number of Auxiliary Contacts NC 0
Standards IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-16, UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Operational Voltage Main Circuit 690 V
Rated Frequency (f) Control Circuit 50 / 60 Hz
Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 50 A
Rated Operational Current AC-1 (I_e) (690 V) 40 °C 45 A
(690 V) 60 °C 40 A
(690 V) 70 °C 32 A
Rated Operational Current AC-3 (I_e) (415 V) 60 °C 26 A
(440 V) 60 °C 26 A
(500 V) 60 °C 23 A
(690 V) 60 °C 17 A
(380 / 400 V) 60 °C 26 A
(220 / 230 / 240 V) 60 °C 26 A
Rated Operational Current AC-3e (I_e) (415 V) 60 °C 26 A
(440 V) 60 °C 26 A
(500 V) 60 °C 23 A
(690 V) 60 °C 17 A
(380 / 400 V) 60 °C 26 A
(220 / 230 / 240 V) 60 °C 26 A
Rated Operational Current DC-1 (I_e) (110 V) 2 Poles in Series, 40 °C 45 A
(110 V) 2 Poles in Series, 60 °C 40 A
(110 V) 2 Poles in Series, 70 °C 32 A
(110 V) 3 Poles in Series, 40 °C 45 A
(110 V) 3 Poles in Series, 60 °C 40 A
(110 V) 3 Poles in Series, 70 °C 32 A
(220 V) 3 Poles in Series,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / AF26-30-00-41 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.