

**INDUSTRIAL COMPONENT DATA**

# 1SFL667001R7011 ABB AF2650-30-11 100-250V 50/60Hz / 100-250 DC Contactor

Brand: ABB | Manufacturer Part Number: 1SFL667001R7011



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | 1SFL667001R7011               |
| Catalog number  | 667001                        |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-91187A9E43                 |
| Generated       | 2026-08-05                    |

## Product Overview

AF2650-30-11 100-250V 50/60Hz / 100-250 DC Contactor

AF2650-30-11 CONT. 3P BOB 100-250VAC/DC

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                   |
|--------------|---------------------------------------------------|
| Catalog path | ABB > Contactors and overload relays > "A" SECRLP |
|--------------|---------------------------------------------------|

## Additional Product Information

### Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

### Popular Downloads

EPLAN Data 9AAC174543\_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Data Sheet, Technical Information (Part 2) 1SAC200017M0002

Instructions and Manuals 1SFC101050M0201

CAD Dimensional Drawing 2CDC001079B0201

### Dimensions

Product Net Width 438 mm

Product Net Depth / Length 244 mm

Product Net Height 422 mm

Product Net Weight 43 kg

**Technical**

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Auxiliary Contacts NC 1

Number of Poles 3P

Rated Operational Voltage Main Circuit 1000 V

Rated Frequency (f) Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 2650 ARated Operational Current AC-1 (I<sub>e</sub>) (1000 V) 40 °C 2650 A

(1000 V) 55 °C 2350 A

(1000 V) 70 °C 2120 A

(690 V) 40 °C 2650 A

(690 V) 55 °C 2350 A

(690 V) 70 °C 2120 A

Rated Operational Current DC-1 (I<sub>e</sub>) (110 V) 1-Pole, 70 °C 2650 A

(110 V) 2 Poles in Series, 70 °C 2650 A

(110 V) 3 Poles in Series, 70 °C 2650 A

(220 V) 3 Poles in Series, 40 °C 2650 A

(220 V) 3 Poles in Series, 70 °C 2650 A

(260 V) 3 Poles in Series, 70 °C 2650 A

(300 V) 3 Poles in Series, 70 °C 2650 A

(340 V) 3 Poles in Series, 70 °C 2650 A

(600 V) 3 Poles in Series, 40 °C 2650 A

(72 V) 1-Pole, 70 °C 2650 A

(72 V) 2 Poles in Series, 70 °C 2650 A

(72 V) 3 Poles in Series, 70 °C 2650 A

(850 V) 3 Poles in Series, 40 °C 2650 A

Rated Making Capacity AC-3 10....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / 1SFL667001R7011 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.