

**INDUSTRIAL COMPONENT DATA**

# 1SBL237561R1400 ABB

## AF26B-22-00CONT.TRACBOB.250-500VAC-DC

Brand: ABB | Manufacturer Part Number: 1SBL237561R1400



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | 1SBL237561R1400               |
| Catalog number  | 237561                        |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-98E644161C                 |
| Generated       | 2026-08-03                    |

### Product Overview

AF26B-22-00CONT.TRACBOB.250-500VAC-DC  
AF26B-22-00-14 250-500V50/60HZ-DC Contactor

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      ABB &gt; Contactors and overload relays &gt; AF contactors to 38 A

### Additional Product Information

**Ordering**

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

**Popular Downloads**

Data Sheet, Technical Information 1SBC100220C0201

Instructions and Manuals 1SBC101027M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

**Dimensions**

Product Net Width 45 mm

Product Net Depth / Length 101 mm

Product Net Height 86 mm

Product Net Weight 0.41 kg

**Technical**

Number of Main Contacts NO 2

Number of Main Contacts NC 2

Number of Auxiliary Contacts NO 0

Number of Auxiliary Contacts NC 0

Number of Poles 4P

Standards IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.

Rated Operational Voltage Main Circuit 690 V

Rated Frequency (f) Control Circuit 50 / 60 Hz

Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 55 A

Rated Operational Current AC-1 (I<sub>e</sub>) (1000 V) 60 °C 40 A

(690 V) 40 °C 45 A

(690 V) 70 °C 32 A

Rated Operational Current AC-3 (I<sub>e</sub>) (415 V) 60 °C 21.2 A

(440 V) 60 °C 20 A

(500 V) 60 °C 17.6 A

(690 V) 60 °C 10.5 A

(380 / 400 V) 60 °C 22 A

(220 / 230 / 240 V) 60 °C 23.2 A

Rated Operational Power AC-3 (P<sub>e</sub>...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL237561R1400 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.