

## INDUSTRIAL COMPONENT DATA

## 1SBL296001R2022 ABB AF38Z-30-22-20 12-20VDC Contactor

Brand: ABB | Manufacturer Part Number: 1SBL296001R2022



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | 1SBL296001R2022               |
| Catalog number  | 296001                        |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-41E93FDD8F                 |
| Generated       | 2026-08-03                    |

## Product Overview

AF38Z-30-22-20 12-20VDC Contactor

AF38Z-30-22-20 CONT. 3P BOB 12-20VDC

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Contactors and overload relays &gt; AF contactors to 38 A

## Additional Product Information

## Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

## Popular Downloads

EPLAN Data 9AAC159650\_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101027M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

## Dimensions

Product Net Width 45 mm

Product Net Depth / Length 119.5 mm

Product Net Height 86 mm

Product Net Weight 0.4 kg

## Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 2

Number of Auxiliary Contacts NC 2

Number of Poles 3P

Standards IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1

Rated Operational Voltage Auxiliary Circuit 690 V

Main Circuit 690 V

Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz

Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 50 A  
acc. to IEC 60947-5-1, ? = 40 °C 16 A

Rated Operational Current AC-1 (I<sub>e</sub>) (690 V) 40 °C 50 A

(690 V) 60 °C 42 A

(690 V) 70 °C 37 A

Rated Operational Current AC-3 (I<sub>e</sub>) (415 V) 60 °C 38 A

(440 V) 60 °C 38 A

(500 V) 60 °C 33 A

(690 V) 60 °C 24 A

(380 / 400 V) 60 °C 38 A

(220 / 230 / 240 V) 60 °C 40 A

Rated Operational Current AC-3e (I<sub>e</sub>) (415 V) 60 °C 38 A

(440 V) 60 °C 38 A

(500 V) 60 °C 33 A

(690 V) 60 °C 24 A

(380 / 400 V) 60 °C 38 A

(220 / 230 / 240 V) 60 °C 40 A

Rated Operational Current AC-15 (I<sub>e</sub>) (500 V) 2 A

(690 V) 2 A

(24 / 127 V)...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL296001R2022 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.