

INDUSTRIAL COMPONENT DATA

1SFL617001R6911 ABB AF580-30-11 48-130V 50/60Hz / 48-130V DC Contactor

Brand: ABB | Manufacturer Part Number: 1SFL617001R6911



Manufacturer	ABB
MPN / Reference	1SFL617001R6911
Catalog number	617001
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-9A1BA69CF9
Generated	2026-08-05

Product Overview

AF580-30-11 48-130V 50/60Hz / 48-130V DC Contactor

AF580-30-11 CONT. 3P 580A BOB.48-130Va/c

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > "A" SECRLP

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

EPLAN Data 9AAC200768_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Data Sheet, Technical Information (Part 2) 1SAC200017M0002

Instructions and Manuals 1SFC380023-en

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 210 mm

Product Net Depth / Length 242 mm

Product Net Height 283 mm

Product Net Weight 13.6 kg

Dimension Diagram 53540919-60

Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Auxiliary Contacts NC 1

Number of Poles 3P

Rated Operational Voltage Main Circuit 1000 V

Rated Frequency (f) Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 800 A

Rated Operational Current AC-1 (I_e) (1000 V) 40 °C 800 A

(1000 V) 55 °C 700 A

(1000 V) 70 °C 580 A

(690 V) 40 °C 800 A

(690 V) 55 °C 700 A

(690 V) 70 °C 580 A

Rated Operational Current AC-3 (I_e) (415 V) 55 °C 580 A

(440 V) 55 °C 580 A

(500 V) 55 °C 580 A

(690 V) 55 °C 500 A

(1000 V) 55 °C 250 A

(380 / 400 V) 55 °C 580 A

(220 / 230 / 240 V) 55 °C 580 A

Rated Operational Current DC-1 (I_e) (110 V) 1-Pole, 40 °C 800 A

(110 V) 2 Poles in Series, 40 °C 800 A

(220 V) 3 Poles in Series, 40 °C 800 A

(600 V) 3 Poles in Series, 40 °C 800 A

(850 V) 3 Poles in Series, 40 °C 800 A

Rated Operational Current DC-3 (I_e) (110 V) 1-Pole, 40 °C 800 A

(110 V) 2 Poles in Series, 40 °C 800 A

(220 V) 3 Poles in S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFL617001R6911 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.