

INDUSTRIAL COMPONENT DATA

GJL1213209R0005 ABB BC6-40-00-P-05 Mini Contactor 220-240VDC

Brand: ABB | Manufacturer Part Number: GJL1213209R0005



Manufacturer	ABB
MPN / Reference	GJL1213209R0005
Catalog number	1213209
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-FC97FFEA4E
Generated	2026-08-05

Product Overview

BC6-40-00-P-05 Mini Contactor 220-240VDC

BC6-40-00-P MINICONT. 220-240Vdc

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Minicontactors B6-B7

Additional Product Information

The BC6-40-00-P mini contactor is a compact 4 pole contactor with soldering pins. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the noiseless and hum-free coil and a switch position indication.

+-Accessories

Identifier Description Type Qty Unit Of Measure

GJL1201319R0002

CA6-11E-P Auxiliary Contact CA6-11E-P 1 piece

GJL1201319R0003

CA6-11M-P CA6-11M-P Auxiliary Contact 1 piece

GJL1201319R0004

CA6-11N-P CA6-11N-P Auxiliary Contact 1 piece

Ordering

EAN:4013614326707

Minimum Order Quantity:1 piece

Customs Tariff Number:85365080

Dimensions

Product Net Width:47.5mm

Product Net Height:45.5mm

Product Net Depth:51.5mm

Product Net Weight:0.17kg

Container Information

Package Level 1 Units:10 piece

Package Level 1 Width:108 mm

Package Level 1 Height:69 mm

Package Level 1 Length:247 mm

Package Level 1 Gross Weight:1.775 kg

Package Level 1 EAN:4013614415456

Technical

Number of Poles:4

Mini Contactor Type:Mini Contactor

Rated Operational Voltage:Main Circuit 12 ... 690 V AC/DC

Main Circuit 690 V AC

Rated Frequency (f):Control Circuit DC

Main Circuit 60 Hz

Main Circuit 50 Hz

Main Circuit DC

Rated Impulse Withstand Voltage (Uimp):Main Circuit 6 kV

Rated Insulation Voltage (Ui):690 V

acc. to UL/CSA 600 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1213209R0005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.