

## INDUSTRIAL COMPONENT DATA

## GJL1201318R0002 ABB CA6-11E-F Auxiliary Contact

Brand: ABB | Manufacturer Part Number: GJL1201318R0002



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | ABB                     |
| MPN / Reference | GJL1201318R0002         |
| Catalog number  | 1201318                 |
| Category        | Auxiliary contact block |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-347DD5CFA1           |
| Generated       | 2026-08-03              |

## Product Overview

CA6-11E-F Auxiliary Contact

CA6-11EF Contact AUX. LAT. 1NA+1NC

CA6-11E-F Auxiliary Contact 1NO/1NC flat pin, side mounted

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Contactors and overload relays &gt; Minicontactors B6-B7

## Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Popular Downloads

EPLAN Data 9AAC166197\_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 2CDC102047M6801

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 20.3 mm

Product Net Depth / Length 46.5 mm

Product Net Height 48.5 mm

Product Net Weight 0.025 kg

Dimension Diagram GJL1200444F0001

**Technical**

Number of Main Contacts NO 0  
Number of Main Contacts NC 0  
Number of Auxiliary Contacts NO 1  
Number of Auxiliary Contacts NC 1  
Number of Poles 2P  
Standards IEC/EN 60947-1  
IEC/EN 60947-4-1  
IEC/EN 60947-5-1  
UL 60947-1  
UL 60947-4-1  
IEC 60335-2-40 A2L  
Rated Operational Voltage Auxiliary Circuit 690 V AC  
Auxiliary Circuit 250 V DC  
Rated Frequency (f) Auxiliary Circuit 50 Hz  
Auxiliary Circuit 60 Hz  
Auxiliary Circuit DC  
Conventional Free-air Thermal Current (I<sub>th</sub>) Auxiliary Circuit 6 A  
Rated Operational Current AC-15 (I<sub>e</sub>) (24 V) 4 A  
(240 V) 4 A  
(500 V) 2 A  
(380 / 400 V) 3 A  
Rated Operational Current DC-13 (I<sub>e</sub>) (24 V) 1.5 A  
(110 V) 0.4 A  
(220 / 240 V) 0.04 A  
Short-Circuit Protective Devices gG Type Fuses 10 A  
Rated Insulation Voltage (U<sub>i</sub>) 690 V  
Rated Impulse Withstand Voltage (U<sub>imp</sub>) Auxiliary Circuit 6 kV  
Maximum Electrical Switching Frequency (AC-15) 600 cycles per hour  
(DC-13) 600 cycles per hour  
Minimum Switching Capacity 17 V  
5 mA  
Power Loss at Rated Operating Conditions per Pole 0.27 W  
Degree of Protection IP20  
Terminal Type Flat-Pin Connections  
Suitable For B6-40-00-F...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / GJL1201318R0002 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.