

INDUSTRIAL COMPONENT DATA

GJL1201318R0002 ABB CA6-11E-F Auxiliary Contact

Brand: ABB | Manufacturer Part Number: GJL1201318R0002



Manufacturer	ABB
MPN / Reference	GJL1201318R0002
Catalog number	1201318
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-347DD5CFA1
Generated	2026-08-05

Product Overview

CA6-11E-F Auxiliary Contact

CA6-11EF Contact AUX. LAT. 1NA+1NC

CA6-11E-F Auxiliary Contact 1NO/1NC flat pin, side mounted

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Minicontactors B6-B7

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Popular Downloads

EPLAN Data 9AAC166197_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 2CDC102047M6801

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 20.3 mm

Product Net Depth / Length 46.5 mm

Product Net Height 48.5 mm

Product Net Weight 0.025 kg

Dimension Diagram GJL1200444F0001

Technical

Number of Main Contacts NO 0
Number of Main Contacts NC 0
Number of Auxiliary Contacts NO 1
Number of Auxiliary Contacts NC 1
Number of Poles 2P
Standards IEC/EN 60947-1
IEC/EN 60947-4-1
IEC/EN 60947-5-1
UL 60947-1
UL 60947-4-1
IEC 60335-2-40 A2L
Rated Operational Voltage Auxiliary Circuit 690 V AC
Auxiliary Circuit 250 V DC
Rated Frequency (f) Auxiliary Circuit 50 Hz
Auxiliary Circuit 60 Hz
Auxiliary Circuit DC
Conventional Free-air Thermal Current (I_{th}) Auxiliary Circuit 6 A
Rated Operational Current AC-15 (I_e) (24 V) 4 A
(240 V) 4 A
(500 V) 2 A
(380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e) (24 V) 1.5 A
(110 V) 0.4 A
(220 / 240 V) 0.04 A
Short-Circuit Protective Devices gG Type Fuses 10 A
Rated Insulation Voltage (U_i) 690 V
Rated Impulse Withstand Voltage (U_{imp}) Auxiliary Circuit 6 kV
Maximum Electrical Switching Frequency (AC-15) 600 cycles per hour
(DC-13) 600 cycles per hour
Minimum Switching Capacity 17 V
5 mA
Power Loss at Rated Operating Conditions per Pole 0.27 W
Degree of Protection IP20
Terminal Type Flat-Pin Connections
Suitable For B6-40-00-F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1201318R0002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.