

## INDUSTRIAL COMPONENT DATA

## GJL1201330R0010 ABB CAF6-02E Auxiliary Contact

Brand: ABB | Manufacturer Part Number: GJL1201330R0010



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | ABB                     |
| MPN / Reference | GJL1201330R0010         |
| Catalog number  | 1201330                 |
| Category        | Auxiliary contact block |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-1AB8E3EFC6           |
| Generated       | 2026-08-03              |

## Product Overview

CAF6-02E Auxiliary Contact

CAF6-02E Contact AUX. FRON. 2NC

CAF6-02E Auxiliary Contact 0NO/2NC screw terminal, front mounted

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Contactors and overload relays &gt; Minicontactors B6-B7

## Additional Product Information

The CAF6-02E is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals.

Ordering

EAN:4013614148385

Minimum Order Quantity:1 piece

Customs Tariff Number:85389099

Container Information

Package Level 1 Width:115 mm

Package Level 1 Length:280 mm

Package Level 1 Height:54 mm

Package Level 1 Gross Weight:0.24 kg

Package Level 1 EAN:4013614412318

Package Level 1 Units:10 piece

Dimensions

Product Net Width:47.5mm

Product Net Height:29mm

Product Net Depth:26.5mm

Product Net Weight:0.02kg

Technical

Rated Operational Voltage:Auxiliary Circuit 12 ... 240 V DC

Auxiliary Circuit 12 ... 500 V AC/DC

Rated Frequency (f):Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Rated Impulse Withstand Voltage (Uimp):Auxiliary Circuit 6 kV

Rated Insulation Voltage (Ui):690 V

Degree of Protection:IP20

Connecting Capacity-Auxiliary Circuit:Flexible with Ferrule 1/2x 1 ... 2.5 mm<sup>2</sup>

Flexible 1/2x 1 ... 2.5 mm<sup>2</sup>

Rigid 1/2x 1 ... 4 mm<sup>2</sup>

Tightening Torque:Auxiliary Circuit 0.8 ... 1.1 N·m

Wire Stripping Length:Auxiliary Circuit 9 mm

Standards:IEC/EN 60947-1

IEC/EN 60947-4-1

IEC/EN 60947-5-1

UL 60947-1

UL 60947-4-1

Number of Auxiliary Contacts NO:0

Number of Main Contacts NC:0

Number of Main Contacts NO:0

Conventional Free-air Thermal Current (Ith):Auxiliary Circuit 6 A

Product Name:Auxiliary Contact

Suitable For:B6-30-01

BC6-30-01

B7-30-01

BC7-30-01

VB6-30-01

VBC6-30-01

VB7-30-01

VBC7-30-01

VB6A-30-01

VBC6A-30-01

VB7A-30-01

VBC7A-30-01

Suitable for Product Class:...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1201330R0010 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.