

INDUSTRIAL COMPONENT DATA

GJL1201330R0005 ABB CAF6-20K Auxiliary Contact

Brand: ABB | Manufacturer Part Number: GJL1201330R0005



Manufacturer	ABB
MPN / Reference	GJL1201330R0005
Catalog number	1201330
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-61FB1C9813
Generated	2026-08-01

Product Overview

CAF6-20K Auxiliary Contact

CAF6-20K AUX Contact. FRON. 2nd

CAF6-20K Auxiliary Contact 2NO/0NC screw terminal, front mounted

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Minicontactors B6-B7

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 2CDC102005M0101

Instructions and Manuals (Part 2) 2CDC102005M0101

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 47.5 mm

Product Net Depth / Length 26.5 mm

Product Net Height 29 mm

Product Net Weight 0.02 kg

Dimension Diagram GJL1200446F0001

Technical

Number of Main Contacts NO 0
Number of Main Contacts NC 0
Number of Auxiliary Contacts NO 2
Number of Auxiliary Contacts NC 0
Number of Poles 2P
Standards IEC/EN 60947-1
IEC/EN 60947-4-1
IEC/EN 60947-5-1
UL 60947-1
UL 60947-4-1
IEC 60335-2-40 A2L
Rated Operational Voltage Auxiliary Circuit 690 V AC
Auxiliary Circuit 250 V DC
Rated Frequency (f) Auxiliary Circuit 50 Hz
Auxiliary Circuit 60 Hz
Auxiliary Circuit DC
Conventional Free-air Thermal Current (I_{th}) Auxiliary Circuit 6 A
Rated Operational Current AC-15 (I_e) (24 V) 4 A
(240 V) 4 A
(500 V) 2 A
(380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e) (24 V) 1.5 A
(110 V) 0.4 A
(220 / 240 V) 0.04 A
Short-Circuit Protective Devices gG Type Fuses 10 A
Rated Insulation Voltage (U_i) 690 V
Rated Impulse Withstand Voltage (U_{imp}) Auxiliary Circuit 6 kV
Maximum Electrical Switching Frequency (AC-15) 600 cycles per hour
(DC-13) 600 cycles per hour
Minimum Switching Capacity 17 V
5 mA
Power Loss at Rated Operating Conditions per Pole 0.27 W
Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1201330R0005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.