

## INDUSTRIAL COMPONENT DATA

## GJL1201330R0008 ABB CAF6-20N Auxiliary Contact

Brand: ABB | Manufacturer Part Number: GJL1201330R0008



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | ABB                     |
| MPN / Reference | GJL1201330R0008         |
| Catalog number  | 1201330                 |
| Category        | Auxiliary contact block |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-306D89C86D           |
| Generated       | 2026-08-02              |

## Product Overview

CAF6-20N Auxiliary Contact  
CAF6-20N AUX Contact. FRON. 2nd  
CAF6-20N Auxiliary Contact 2NO/0NC screw terminal, front mounted

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path      ABB > Contactors and overload relays > Minicontactors B6-B7

## Additional Product Information

Ordering  
Minimum Order Quantity 1 piece  
Customs Tariff Number 85365080  
Popular Downloads  
EPLAN Data 9AAC166197\_EPLAN  
Data Sheet, Technical Information 1SBC100214C0202  
Instructions and Manuals 2CDC102005M0101  
Instructions and Manuals (Part 2) 2CDC102005M0101  
CAD Dimensional Drawing 2CDC001079B0201  
Dimensions  
Product Net Width 47.5 mm  
Product Net Depth / Length 26.5 mm  
Product Net Height 29 mm  
Product Net Weight 0.02 kg

Dimension Diagram GJL1200446F0001

Technical

Number of Main Contacts NO 0

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 2

Number of Auxiliary Contacts NC 0

Number of Poles 2P

Standards IEC/EN 60947-1

IEC/EN 60947-4-1

IEC/EN 60947-5-1

UL 60947-1

UL 60947-4-1

IEC 60335-2-40 A2L

Rated Operational Voltage Auxiliary Circuit 690 V AC

Auxiliary Circuit 250 V DC

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Conventional Free-air Thermal Current (I<sub>th</sub>) Auxiliary Circuit 6 A

Rated Operational Current AC-15 (I<sub>e</sub>) (24 V) 4 A

(240 V) 4 A

(500 V) 2 A

(380 / 400 V) 3 A

Rated Operational Current DC-13 (I<sub>e</sub>) (24 V) 1.5 A

(110 V) 0.4 A

(220 / 240 V) 0.04 A

Short-Circuit Protective Devices gG Type Fuses 10 A

Rated Insulation Voltage (U<sub>i</sub>) 690 V

Rated Impulse Withstand Voltage (U<sub>imp</sub>) Auxiliary Circuit 6 kV

Maximum Electrical Switching Frequency (AC-15) 600 cycles per hour

(DC-13) 600 cycles per hour

Minimum Switching Capacity 17 V

5 mA

Power Loss at Rated Operating Conditions per Pole 0.27 W

Connecting Capacity Auxiliary Circuit...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1201330R0008 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.