

INDUSTRIAL COMPONENT DATA

1SBN010151R1311 ABB CAT4-11U Auxiliary Contact / Coil Terminal Block

Brand: ABB | Manufacturer Part Number: 1SBN010151R1311



Manufacturer	ABB
MPN / Reference	1SBN010151R1311
Catalog number	010151
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-7905327C35
Generated	2026-08-03

Product Overview

CAT4-11U Auxiliary Contact / Coil Terminal Block
CAT4-11U BLOCK CONT. AUX AND TERM. BOB.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > AF contactors to 38 A

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85389099

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101041M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 45 mm

Product Net Depth / Length 31.6 mm

Product Net Height 43 mm

Product Net Weight 0.04 kg

Technical

Number of Auxiliary Contacts NO 1

Number of Auxiliary Contacts NC 1

Number of Poles 2P

Standards IEC/EN 60947-5-1, UL 60335-2-40 LZGH2 A2L, UL 60947-5-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-5-1-14

Rated Operational Voltage Auxiliary Circuit 690 V

Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz

Control Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 16 A

Rated Operational Current AC-15 (I_e) (500 V) 2 A

(690 V) 2 A

(24 / 127 V) 6 A

(220 / 240 V) 4 A

(400 / 440 V) 3 A

Rated Operational Current DC-13 (I_e) (24 V) 6 A / 144 W

(48 V) 2.8 A / 134 W

(72 V) 1 A / 72 W

(110 V) 0.55 A / 60 W

(125 V) 0.55 A / 69 W

(220 V) 0.27 A / 60 W

(250 V) 0.27 A / 68 W

(400 V) 0.15 A / 60 W

(500 V) 0.13 A / 65 W

(600 V) 0.1 A / 60 W

Rated Short-time Withstand Current Low Voltage (I_{cw}) for 0.1 s 140 A
for 1 s 100 A

Rated Insulation Voltage (U_i) acc. to IEC 60947-5-1 690 V
acc. to UL/CSA 600 V

Rated Impulse Withstand Voltage (U_{imp}) 6 kV

Maximum Electrical Switching Frequency (AC-15) 1200 cycles per hour

(DC-13) 900 cycles per hour

Maximum....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBN010151R1311 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.