

**INDUSTRIAL COMPONENT DATA**

# 1SFA619402R1004 ABB PILOT ALL-IN-ONE BLUE

Brand: ABB | Manufacturer Part Number: 1SFA619402R1004



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | ABB                      |
| MPN / Reference | 1SFA619402R1004          |
| Catalog number  | 619402                   |
| Category        | Indicator light complete |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-A276189192            |
| Generated       | 2026-07-29               |

## Product Overview

PILOT ALL-IN-ONE BLUE  
BLUE ALL-IN-ONE PILOT  
CL-100L Pilot Light

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                             |
|--------------|-----------------------------|
| Catalog path | ABB > Command and signaling |
|--------------|-----------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece

Customs Tariff Number 8536619090

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_

Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 0.03 m

Product Net Height 0.03 m

Product Net Depth / Length 0.055 m

Product Net Weight 0.018 kg

**Technical**

Ambient Air Temperature Operation -25 ... +70 °C

Storage -40 ... +85 °C

Color Blue  
Actuator Type Pilot light head  
Illumination Illuminated  
Lamp Type Ba9s  
Enclosure Type NEMA Type1  
Type12  
Type13  
Type3R  
Type4  
Type4X  
Pollution Degree 3  
Rated Frequency (f) Supply Circuit 60 50 Hz  
Rated Operational Voltage Maximum 240 V  
Rated Operational Current AC-15 (Ie) (24 / 127 V) 1.5 A  
(220 / 240 V) 1 A  
Connecting Capacity Flexible with Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible 1 x 0.75 ... 2.5 mm<sup>2</sup>  
Flexible 2 x 0.75 ... 2.5 mm<sup>2</sup>  
Solid 1 x 0.75...2.5 mm<sup>2</sup>  
Solid 2 x 0.75...2.5 mm<sup>2</sup>  
Connection Type Screw Clamp  
Terminal Type Screw Terminals  
Tightening Torque 0.9 N·m  
Wire Stripping Length 8 mm  
Suitable For Bulb 3W max.  
Suitable for Product Class Pilot Devices  
Technical UL/CSA  
Connecting Capacity UL/CSA 1x 18...14 AWG  
2x 18...14 AWG  
Environmental  
Degree of Protection Front IP66  
Front IP67  
Front IP69K  
Terminals IP20  
Material Compliance  
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658  
REACH Declaration 2CMT2022-006479  
RoHS Declaration 2CMT2022-...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619402R1004 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.