

INDUSTRIAL COMPONENT DATA

1SVR730884R3300 ABB CM-MPS.41S Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3 3x300-500VAC

Brand: ABB | Manufacturer Part Number: 1SVR730884R3300



Manufacturer	ABB
MPN / Reference	1SVR730884R3300
Catalog number	730884
Category	Phase monitoring relay
Minimum order	1 Pcs
Document ID	EO-F73D6618A6
Generated	2026-08-06

Product Overview

CM-MPS.41S Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x300-500VAC

CM-MPS.41S CTRL THREE-PHASE 2 C/C TOR RELAY

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays > Monitoring

Additional Product Information

Ordering

EAN 4016779851862

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 2CDC112206D0201

Instructions and Manuals 1SVC730730M1000

1SVC730730M0000

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 22.5 mm

Product Net Height 85.6 mm

Product Net Depth / Length 103.7 mm

Product Net Weight 0.14 kg

Technical

Function Phase failure detection
Phase sequence monitoring
Over- and undervoltage monitoring
Phase unbalance detection
Measuring Range (L-L) 300 ... 500 V AC
Time Range Tripping Delay (ON or OFF) 0 second [unit of time]
Rated Control Supply Voltage (Us) (L-L) 300 ... 500 V AC
Rated Frequency (f) Supply Circuit 50/60 Hz
Output 2 C/O Contacts
Terminal Type Screw Terminals
Rated Operational Current AC-12 (Ie) (230 V) 4 A
Rated Operational Current AC-15 (Ie) (230 V) 3 A
Rated Operational Current DC-12 (Ie) (24 V) 4 A
Rated Operational Current DC-13 (Ie) (24 V) 2 A
Minimum Switching Capacity 24 V
10 mA
Rated Impulse Withstand Voltage (Uimp) Input Circuit 6 kV
Output Circuit 4 kV
Rated Insulation Voltage (Ui) Input Circuit / Output Circuit 600 V
Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection Housing IP50
Terminals IP20
Overvoltage Category III
Pollution Degree 3
Short-Circuit Protective Devices Output Circuit NC - F Type Fuses 6 A
Output Circuit NO - F Type Fuses 10 A
Electrical Durability AC-12 100000 cycle
Mechanical Durability Nr. Operations 30000000 cycle
Connecting Capacity FI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR730884R3300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.