

INDUSTRIAL COMPONENT DATA

1SVR730700R2200 ABB CM-MSS.23S Therm. motor protec. relay 2c/o, 110-130VAC/220-240VAC

Brand: ABB | Manufacturer Part Number: 1SVR730700R2200



Manufacturer	ABB
MPN / Reference	1SVR730700R2200
Catalog number	730700
Category	Relay for thermistor protection (PTC)
Minimum order	1 Pcs
Document ID	EO-0DB8898E04
Generated	2026-08-04

Product Overview

CM-MSS.23S Therm. motor protec. relay 2c/o, 110-130VAC/220-240VAC

CM-MSS.23S MOTOR CONTROL RELAY x PTC

CM-MSS.23S Therm. Protec. 2C/O relay, 110-130VAC/220-240VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays > Monitoring

Additional Product Information

The CM-MSS.23S belongs to the CM-MSS thermistor motor protection relay range. It operates with a rated control supply voltage of 110-130 V AC and 220-240 V AC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It features one sensor circuit to monitor PTC temperature sensors and works according to the closed-circuit principle. The relay can be reset automatically, manually or remotely after the failure has been removed. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Ordering

EAN:4013614496691

Minimum Order Quantity:1 piece

Customs Tariff Number:85364900

Dimensions

Product Net Width:22.5mm

Product Net Height:85.6mm

Product Net Depth:103.7mm

Product Net Weight:0.174kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:97 mm

Package Level 1 Height:109 mm

Package Level 1 Length:30 mm

Package Level 1 Gross Weight:0.197 kg

Technical

Function:1 sensor circuit

Auto, manual or remote reset

Rated Control Supply Voltage (Us):110 ... 130 V AC

220 ... 240 V AC

Output:2 c/o (SPDT) contacts

Terminal Type:Screw Terminals

Rated Operational Current AC-12 (Ie):(230 V) 4 A

Rated Operational Current AC-15 (Ie):(230 V) 3 A

Rated Operational Current DC-12 (Ie):(24 V) 4 A

Rated Operational Current DC-13 (Ie):(24 V) 2 A

Minimum Switching Capacity:24 V

10 mA

Rated Insulation Voltage (Ui):300 V

Measuring Circuit / Output...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR730700R2200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.