

INDUSTRIAL COMPONENT DATA

1SVR740840R0400 ABB CM-SRS.21P Current monitoring relay 2c/o, B-C 3mA-1A RMS, 24-240VAC/DC

Brand: ABB | Manufacturer Part Number: 1SVR740840R0400



Manufacturer	ABB
MPN / Reference	1SVR740840R0400
Catalog number	740840
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-E8E7A9BD12
Generated	2026-08-06

Product Overview

CM-SRS.21P Current monitoring relay 2c/o, B-C=3mA-1A RMS, 24-240VAC/DC

CM-SRS.21P RELe CTRL CURRENT 2 C/C RES

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays > Monitoring

Additional Product Information

The CM-SRS.21P is a single-functional current monitoring relay from the CM single-phase monitors range. This monitoring relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. It provides a RMS measuring principle for DC and AC currents with 3 measuring ranges: 3-30 mA, 10-100 mA and 0.1-1 A and works according to the open-circuit principle. The CM-SRS.21P is configurable for over- or undercurrent monitoring. The hysteresis is adjustable within a range of 3 to 30 % of the threshold value and the tripping delay is adjustable over a range of instantaneous to 30 s (0, 0.1-30 s). A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering

EAN:4016779852487

Minimum Order Quantity:1 piece

Customs Tariff Number:85364900

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:97 mm

Package Level 1 Height:109 mm

Package Level 1 Length:30 mm

Package Level 1 Gross Weight:0.163 kg

Dimensions

Product Net Width:22.5mm

Product Net Depth:103.7mm

Product Net Height:85.6mm

Product Net Weight:0.141kg

Technical

Function:Over- or undercurrent monitoring

Measuring Range:3 ... 30 mA

10 ... 100 mA

0.1 ... 1 A

Rated Control Supply Voltage (Us):24 ... 240 V AC/DC

Output:2 c/o (SPDT) contacts

Time Range:0 s or 0.1-30 s tripping delay (ON)

Terminal Type:Screwless Terminals....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR740840R0400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.