

INDUSTRIAL COMPONENT DATA

1SVR740740R9200 ABB CM-TCS.22P Temperature monitoring relay Temp.-range 0...+100°C, 24VAC/DC

Brand: ABB | Manufacturer Part Number: 1SVR740740R9200



Manufacturer	ABB
MPN / Reference	1SVR740740R9200
Catalog number	740740
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-BEDF551BF1
Generated	2026-08-05

Product Overview

CM-TCS.22P Temperature monitoring relay Temp.-range 0...+100°C, 24VAC/DC

CM-TCS.22P RELe CTL TEMP 0/100°C 2 C/C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays > Monitoring

Additional Product Information

CM-TCS.22P Temperature monitoring relay Temp.-range 0...+100°C, 24VAC/DC

Ordering

EAN:4016779852814

Minimum Order Quantity:1 piece

Customs Tariff Number:85364900

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:97 mm

Package Level 1 Height:109 mm

Package Level 1 Length:30 mm

Package Level 1 Gross Weight:0.152 kg

Dimensions

Product Net Width:22.5mm

Product Net Depth:103.7mm

Product Net Height:85.6mm
Product Net Weight:0.127kg
Technical
Function:Overtemperature monitoring
Undertemperature monitoring
Over- and undertemperature monitoring
1 sensor circuit
Short-circuit detection
Measuring Range:0 ... +100 °C
Rated Control Supply Voltage (Us):24 V AC/DC
Output:2 x 1 c/o or 1 x 2 c/o contacts, configurable
Terminal Type:Screwless Terminals
Rated Operational Current AC-12 (Ie):(230 V) 4 A
Rated Operational Current AC-15 (Ie):(230 V) 3 A
Rated Operational Current DC-12 (Ie):(24 V) 4 A
Rated Operational Current DC-13 (Ie):(24 V) 2 A
Minimum Switching Capacity:24 V
10 mA
Rated Impulse Withstand Voltage (Uimp):Input Circuit 6 kV
Output Circuit 4 kV
Degree of Protection:Housing IP50
Terminals IP20
Overvoltage Category:III
Pollution Degree:3
Short-Circuit Protective Devices:Output Circuit NC - F Type Fuses 6 A
Output Circuit NO - F Type Fuses 10 A
Electrical Durability:AC-12 100000 cycle
Connecting Capacity:Flexible with Ferrule 2x 0.5 ... 1.5 mm²
Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm²
Flexible 2x 0.5 ... 1.5 mm²
Rigid 2x 0.5 ... 1.5 mm²
Wire Strippin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR740740R9200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.