

## INDUSTRIAL COMPONENT DATA

# 1SFA619403R5138 ABB Compact Pilot Light Clear LED 110-130V AC

Brand: ABB | Manufacturer Part Number: 1SFA619403R5138



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | ABB                      |
| MPN / Reference | 1SFA619403R5138          |
| Catalog number  | 619403                   |
| Category        | Indicator light complete |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-60B3A4CE2F            |
| Generated       | 2026-07-28               |

## Product Overview

Compact Pilot Light Clear LED 110-130V AC  
Compact Pilot. White LED 110-130V AC  
CL2-513C Pilot Light

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB > Command and signaling > elements PDA

## Additional Product Information

### Ordering

Minimum Order Quantity 10 piece

Customs Tariff Number 8536619090

### Popular Downloads

Data Sheet, Technical Information 1SFC151007C02\_\_

Instructions and Manuals 1SFC151011M0201

### Dimensions

Product Net Width 0.03 m

Product Net Height 0.03 m

Product Net Depth / Length 0.052 m

Product Net Weight 0.018 kg

### Technical

Ambient Air Temperature Operation -25 ... +70 °C

Storage -40 ... +85 °C  
Color Clear  
Actuator Type Pilot light head  
Illumination Illuminated  
Lamp Type 110-130 V AC, integrated LED  
Enclosure Type NEMA Type1  
Type12  
Type13  
Type3R  
Type4  
Type4X  
Pollution Degree 3  
Rated Frequency (f) Supply Circuit 50 / 60 Hz  
Rated Operational Voltage 110 ... 130 V AC  
Supply Circuit 110 ... 130 V AC  
Connecting Capacity Flexible with Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible 1 x 0.75 ... 2.5 mm<sup>2</sup>  
Flexible 2 x 0.75 ... 2.5 mm<sup>2</sup>  
Solid 1 x 0.75...2.5 mm<sup>2</sup>  
Solid 2 x 0.75...2.5 mm<sup>2</sup>  
Connection Type Screw Clamp  
Terminal Type Screw Terminals  
Tightening Torque 0.9 N·m  
Wire Stripping Length 8 mm  
Technical UL/CSA  
Connecting Capacity UL/CSA 1x 18...14 AWG  
2x 18...14 AWG  
Environmental  
Degree of Protection Front IP66  
Front IP67  
Front IP69K  
Terminals IP20  
Material Compliance  
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658  
REACH Declaration 2CMT2022-006479  
RoHS Declaration 2CMT2022-006498  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/86...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619403R5138 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.