

INDUSTRIAL COMPONENT DATA

1SVR360060R1001 ABB CP-C.1-A-RU Redundancy unit for power supplies In: 2x20A, Out: 1x40A

Brand: ABB | Manufacturer Part Number: 1SVR360060R1001



Manufacturer	ABB
MPN / Reference	1SVR360060R1001
Catalog number	360060
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-E3765D2D96
Generated	2026-08-05

Product Overview

CP-C.1-A-RU Redundancy unit for power supplies In: 2x20A, Out: 1x40A

CP-C.1-A-RU Redundancy unit for

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85044095

Replacement Product ID (NEW) 1SVR427071R0000

Popular Downloads

Data Sheet, Technical Information 2CDC114103D0201

Instructions and Manuals 1SVC360561M0000

Dimensions

Product Net Width 56.4 mm

Product Net Height 129.4 mm

Product Net Depth / Length 136 mm

Product Net Weight 1.04 kg

Container Information

Package Level 1 Width 90 mm

Package Level 1 Depth / Length 155 mm

Package Level 1 Height 165 mm

Package Level 1 Gross Weight 1.17 kg

Package Level 1 EAN 4013614523816

Package Level 1 Units box 1 piece

Technical

Function Redundancy unit

Rated Input Voltage (UIN) 12 ... 48 V DC

Input Voltage (Uin) 10 ... 58 V DC

Rated Frequency (f) DC

Rated Output Voltage 12 ... 48 V DC

Output Voltage (Uout) 10 ... 58 V DC

Rated Output Current 40 A

Output Current 60 A

Rated Insulation Voltage (Ui) Input Circuit / Output Circuit 60 V

Degree of Protection Housing IP20

Terminals IP20

Pollution Degree 2

Connecting Capacity Input Circuit Flexible with Ferrule 2.5 ... 10 mm²

Flexible 2.5 ... 10 mm²

Rigid 2.5 ... 16 mm²

Connecting Capacity Output Circuit Flexible with Ferrule 2.5 ... 10 mm²

Flexible 2.5 ... 10 mm²

Rigid 2.5 ... 16 mm²

Tightening Torque Input Circuit 1.2 N·m

Output Circuit 1.2 N·m

Wire Stripping Length Input Circuit 10 mm

Output Circuit 10 mm

Recommended Screw Driver Input Circuit / Output Circuit 0.8 x 4

Minimum Mounting Distance Electrical Conductive Board, Horizontal 25 mm

Electrical Conductive Board, Vertical 25 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR360060R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.