

**INDUSTRIAL COMPONENT DATA**

# 1SVR405600R4000 ABB CR-P012DC1 Pluggable interface relay 1c/o, A1-A2 12VDC, 250V/16A

Brand: ABB | Manufacturer Part Number: 1SVR405600R4000



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | ABB             |
| MPN / Reference | 1SVR405600R4000 |
| Catalog number  | 405600          |
| Category        | Switching relay |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-E5F0E91A44   |
| Generated       | 2026-08-04      |

## Product Overview

CR-P012DC1 Pluggable interface relay 1c/o, A1-A2=12VDC, 250V/16A

CR-P012DC1 plug-in relays

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB &gt; Electronic relays &gt; Plug-in

## Additional Product Information

**Ordering**

EAN 4013614498176

Minimum Order Quantity 10 piece

Customs Tariff Number 85364900

**Popular Downloads**

Data Sheet, Technical Information 2CDC110004C0210\_05

Instructions and Manuals 1SVC405600M9000

CAD Dimensional Drawing 2CDC001079B0201

EPLAN Data 9AAC132576\_EPLAN

**Dimensions**

Product Net Width 12.7 mm

Product Net Height 15.7 mm

Product Net Depth / Length 29 mm

Product Net Weight 0.014 kg

**Technical**

Function Pluggable pcb interface relay CR-P

Sub-Function Relay w/o built in LED

Rated Control Supply Voltage (Us) 12 V DC

Rated Operational Voltage 400 V AC

Rated Frequency (f) 50 / 60 Hz

Output 1 C/O (SPDT) Contact

Output Signal 250 V / 16 A

Terminal Type Soldering Pins

Rated Operational Current AC-12 (Ie) (230 V) 16 A

Rated Operational Current AC-15 (Ie) (120 V) 3 A  
(230 V) 1.5 A

Rated Operational Current DC-12 (Ie) (24 V) 16 A

Rated Operational Current DC-13 (Ie) (24 V) 2.5 A  
(250 V) 0.1 A

Rated Insulation Voltage (Ui) 400 V

Degree of Protection IP67

Mounting Position 1

Standards IEC/EN 61810-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA 300 V AC

Pilot Duty UL/CSA B300

Flammability According to UL94 V-0

**Environmental**

Ambient Air Temperature Operation -40 ... +85 °C

Storage -40 ... +85 °C

Maximum Operating Altitude Permissible Without Derating 2000 m

**Material Compliance**

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SVD981001-4501

RoHS Declaration 1SVD981001-4401

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 Ju...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / 1SVR405600R4000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.