

## INDUSTRIAL COMPONENT DATA

# 1SVR740110R3300 ABB CT-AHS.22P Time relay, OFF-delay 2c/o, 24-48VDC, 24-240VAC

Brand: ABB | Manufacturer Part Number: 1SVR740110R3300



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | ABB             |
| MPN / Reference | 1SVR740110R3300 |
| Catalog number  | 740110          |
| Category        | Timer relay     |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-7CDD32D20C   |
| Generated       | 2026-08-06      |

## Product Overview

CT-AHS.22P Time relay, OFF-delay 2c/o, 24-48VDC, 24-240VAC

CT-AHS.22P TEMPO RET. DISCONNECTION. 2 C/C RE

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Electronic relays &gt; CTS Time

## Additional Product Information

## Ordering

EAN 4016779851688

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

## Popular Downloads

Data Sheet, Technical Information 2CDC110004C0210\_01

Instructions and Manuals 1SVC730050M1000

1SVC730050M0000

CAD Dimensional Drawing 2CDC001079B0201

EPLAN Data 9AAC201310\_EPLAN

## Dimensions

Product Net Width 22.5 mm

Product Net Height 85.6 mm

Product Net Depth / Length 103.7 mm

Product Net Weight 0.125 kg  
Technical  
Timer Relay Type OFF-Delay  
Time Range 0.05 s ... 300 h  
Rated Control Supply Voltage (Us) 24 ... 240 V AC  
24 ... 48 V DC  
Rated Operational Voltage Auxiliary Circuit 250 V  
Rated Frequency (f) 50 / 60 Hz  
DC  
Output 2 C/O Contacts  
Terminal Type Screwless Terminals  
Rated Operational Current AC-12 (Ie) (230 V) 4 A  
Rated Operational Current AC-15 (Ie) (230 V) 3 A  
Rated Operational Current DC-12 (Ie) (24 V) 4 A  
Rated Operational Current DC-13 (Ie) (24 V) 2 A  
Minimum Switching Capacity 12 V  
100 mA  
Rated Impulse Withstand Voltage (Uimp) Input Circuit 4 kV  
Output Circuit 1 / Output Circuit 2 4 kV  
Rated Insulation Voltage (Ui) Input Circuit / Output Circuit 500 V  
Output Circuit 1 / Output Circuit 2 300 V  
Degree of Protection Housing IP50  
Terminals IP20  
Overvoltage Category III  
Pollution Degree 3  
Short-Circuit Protective Devices Output Circuit NC - F Type Fuses 6 A  
Output Circuit NO - F Type Fuses 10 A  
Electrical Durability AC-12 100000 cycle  
Mechanical Durability Nr. Operations 30000000 cycle  
Connecting Capacity Flexible with Ferrule 2x 0.5 ... 1.5 mm<sup>2</sup>  
Flexible with Insula...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR740110R3300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.