

INDUSTRIAL COMPONENT DATA

2CSG225975R1101 ABB CT MAX 600 Current transformer

Brand: ABB | Manufacturer Part Number: 2CSG225975R1101



Manufacturer	ABB
MPN / Reference	2CSG225975R1101
Catalog number	225975
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-7119C8D77B
Generated	2026-08-01

Product Overview

CT MAX 600 Current transformer
Intens transformer. CT MAX 600

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > AER and Transformers > CT
--------------	---------------------------------

Additional Product Information

CT MAX 600 is used to transform primary currents to.../5A secondary currents for c.a. measurement instruments

Ordering

EAN:8012542259756

Minimum Order Quantity:1 piece

Customs Tariff Number:90303100

Dimensions

Product Net Width:0.070m

Product Net Height:0.110m

Product Net Depth:0.045m

Product Net Weight:0.32kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:0.093 m

Package Level 1 Height:0.08 m

Package Level 1 Length:0.143 m

Package Level 1 Gross Weight:0.5 kg

Package Level 1 EAN:8012542259756

Technical

Mounting Type:Through primary

Cable Use:Cable, Horizontal and Vertical bars

Cable Cross-Section:30 mm

Rated Cross-Section:40 x 10 mm

Rated Primary Current (I_{pn}):600 A

Environmental

RoHS Status:Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:ITSCE115CT

RoHS Information:2CSC445004K2701

Classifications

Object Classification Code:P

ETIM 4:EC002048 - Current transformer

ETIM 5:EC002048 - Current transformer

ETIM for 2CSG225975R1101 Low-voltage industrial controls and switchgear (EC002048)

Feature Name

Feature Value

Model (EF000010)

Through-feed current converter

Rated primary current (EF007405)

600 A

Rated secondary current (EF007471)

5 A

Rated secondary apparent power (EF007470)

200 VA

Accuracy class (EF008842)

0.5

Overcurrent limiting factor (EF007511)

FS 5

Calibrated (EF008836)

Yes

With contact protection (EF008186)

Yes

Height opening (EF012757)

12 mm

Width op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSG225975R1101 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.