

INDUSTRIAL COMPONENT DATA

1SVR740211R2300 ABB CT-SDS.23P Time relay, star-delta 2n/o, 380-440VAC

Brand: ABB | Manufacturer Part Number: 1SVR740211R2300



Manufacturer	ABB
MPN / Reference	1SVR740211R2300
Catalog number	740211
Category	Timer relay
Minimum order	1 Pcs
Document ID	EO-C64332D8E8
Generated	2026-08-06

Product Overview

CT-SDS.23P Time relay, star-delta 2n/o, 380-440VAC

CT-SDS.23P TEMPO ESTR-TRIANG 2 N/A RESOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic relays > CTS Time

Additional Product Information

Ordering

EAN 4016779851756

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 2CDC110004C0210_01

Instructions and Manuals 1SVC730050M1000

1SVC730050M0000

CAD Dimensional Drawing 2CDC001079B0201

EPLAN Data 9AAC201310_EPLAN

Dimensions

Product Net Width 22.5 mm

Product Net Height 85.6 mm

Product Net Depth / Length 103.7 mm

Product Net Weight 0.112 kg

Technical

Timer Relay Type Star-Delta

Time Range 0.05 s ... 10 minute [unit of time]

Rated Control Supply Voltage (Us) 380 ... 440 V AC

Rated Operational Voltage Auxiliary Circuit 250 V

Rated Frequency (f) 50 / 60 Hz

Output 2 N/O Contacts

Terminal Type Screwless Terminals

Rated Operational Current AC-12 (Ie) (230 V) 4 A

Rated Operational Current AC-15 (Ie) (230 V) 3 A

Rated Operational Current DC-12 (Ie) (24 V) 4 A

Rated Operational Current DC-13 (Ie) (24 V) 2 A

Minimum Switching Capacity 12 V

100 mA

Rated Impulse Withstand Voltage (Uimp) Input Circuit 4 kV

Output Circuit 1 / Output Circuit 2 4 kV

Rated Insulation Voltage (Ui) Input Circuit / Output Circuit 500 V

Output Circuit 1 / Output Circuit 2 300 V

Degree of Protection Housing IP50

Terminals IP20

Overvoltage Category III

Pollution Degree 3

Short-Circuit Protective Devices Output Circuit NC - F Type Fuses 6 A

Output Circuit NO - F Type Fuses 10 A

Electrical Durability AC-12 100000 cycle

Mechanical Durability Nr. Operations 30000000 cycle

Connecting Capacity Flexible with Ferrule 2x 0.5 ... 1.5 mm²

Flexible with Ins...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SVR740211R2300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.