

INDUSTRIAL COMPONENT DATA

1SEP600119R0002 ABB Desconectador fusible XLP1 250A 4P

Brand: ABB | Manufacturer Part Number: 1SEP600119R0002



Manufacturer	ABB
MPN / Reference	1SEP600119R0002
Catalog number	600119
Category	Fuse switch disconnect
Minimum order	1 Pcs
Document ID	EO-62DA51211D
Generated	2026-08-06

Product Overview

Desconectador fusible XLP1 250A 4P
XLP1 250A 4P fuse disconnect
XLP1-4P-8BC Fuse Switch Disconnect

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches > XLP, SLP
--------------	----------------------------------

Additional Product Information

Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Popular Downloads
Data Sheet, Technical Information 1SEC312012D0201
Instructions and Manuals No Instructions and Manuals needed
Environmental
Degree of Protection IP30
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85389099
Country or Territory of Origin China

Dimensions

Product Net Width 254 mm

Product Net Height 117 mm

Product Net Depth / Length 269 mm

Product Net Weight 2.98 kg

Container Information

Package Level 1 Units shrink-wrap 1 piece

Package Level 1 Width 254 mm

Package Level 1 Depth / Length 269 mm

Package Level 1 Height 117 mm

Package Level 1 Gross Weight 2.98 kg

Package Level 1 EAN 7025840086642

Package Level 2 EAN detach

Technical

Degree of Protection IP30

Device Type Manager (DTM) Fuseswitchdisconnector

Electronic Fuse Monitoring No

Fuse Size NH1

Fuse System DIN

Handle Type Front cover 4P

Mounting Type Baseplate

Number of Poles 4P

Power Loss at Rated Load 7.5 W

Rated Conditional Short-Circuit Current (Inc) (690 V) 50 kiloampere rms

Rated Current (In) 250 A

Rated Frequency (f) Main Circuit 50/60 Hz

Rated Impulse Withstand Voltage (Uimp) Main Circuit 8 kV

Rated Operational Current AC-22B (Ie) (500 V) 250 A

Rated Operational Voltage 500 V AC

Rated Voltage (Ur) 500 V AC

Special Functions Not Included

Standards IEC60947...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SEP600119R0002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.