

INDUSTRIAL COMPONENT DATA

1SBK154037R1400 ABB DRAF12-14P 250-500V50/60HZ DRAF12-14P

Brand: ABB | Manufacturer Part Number: 1SBK154037R1400



Manufacturer	ABB
MPN / Reference	1SBK154037R1400
Catalog number	154037
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-F25028D18B
Generated	2026-08-06

Product Overview

DRAF12-14P 250-500V50/60HZ DRAF12-14P
DRAF12-14P STARTS IN BOX 250-500VAC/DC
DRAF12-14P 250-500V50/60HZ Contactor Starter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Boxed starters

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Product Main Type DRAF12

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101048M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 107 mm

Product Net Depth / Length 131 mm

Product Net Height 230 mm

Product Net Weight 0.82 kg

Technical

Coil Consumption Holding at Max. Rated Control Circuit Voltage 60 Hz 250 V·A

Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²

Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²

Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²

Rigid Solid 1/2x 1 ... 2.5 mm²

Rigid Stranded 1/2x 1 ... 2.5 mm²

Connecting Capacity Control Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²

Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²

Flexible with Insulated Ferrule 1x 0.75 ... 1.5 mm²

Rigid Solid 1/2x 1 ... 2.5 mm²

Rigid Stranded 1/2x 1 ... 2.5 mm²

Connecting Capacity Main Circuit Flexible with Ferrule 1/2x 0.75 ... 6 mm²

Flexible with Insulated Ferrule 1x 0.75 ... 4 mm²

Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm²

Rigid Solid 1/2x 1 ... 4 mm²

Rigid Stranded 1/2x 1 ... 6 mm²

Housing Material ABS

Number of Auxiliary Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Main Contacts NC 0

Number of Main Contacts NO 3

Number of Poles 3P

Pollution Degree 3

Rated Control Circuit Voltage (Uc) 50 Hz 250 ... 500 V

60 Hz 250 ... 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBK154037R1400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.