

INDUSTRIAL COMPONENT DATA

1SBK174237R1100 ABB DRAF16-11S 24-60V50/60HZ DRAF16-11S

Brand: ABB | Manufacturer Part Number: 1SBK174237R1100



Manufacturer	ABB
MPN / Reference	1SBK174237R1100
Catalog number	174237
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-097F8DD10D
Generated	2026-08-03

Product Overview

DRAF16-11S 24-60V50/60HZ DRAF16-11S
DRAF16-11S STARTS IN BOX 24-60VAC/DC
DRAF16-11S 24-60V50/60HZ Contactor Starter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays > Boxed starters
--------------	---

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Product Main Type DRAF16

Popular Downloads

Data Sheet, Technical Information 1SBC100199C0201

Instructions and Manuals 1SBC101048M6801

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 107 mm

Product Net Depth / Length 131 mm

Product Net Height 230 mm

Product Net Weight 0.82 kg

Technical

Coil Consumption Holding at Max. Rated Control Circuit Voltage 60 Hz 24 V·A
Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²
Rigid Solid 1/2x 1 ... 2.5 mm²
Rigid Stranded 1/2x 1 ... 2.5 mm²
Connecting Capacity Control Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 1.5 mm²
Rigid Solid 1/2x 1 ... 2.5 mm²
Rigid Stranded 1/2x 1 ... 2.5 mm²
Connecting Capacity Main Circuit Flexible with Ferrule 1/2x 0.75 ... 6 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 4 mm²
Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm²
Rigid Solid 1/2x 1 ... 4 mm²
Rigid Stranded 1/2x 1 ... 6 mm²
Housing Material ABS
Number of Auxiliary Contacts NC 0
Number of Auxiliary Contacts NO 1
Number of Main Contacts NC 0
Number of Main Contacts NO 3
Number of Poles 3
Pollution Degree 3
Rated Control Circuit Voltage (U_c) 50 Hz 24 ... 60 V
60 Hz 24 ... 60 V
DC Operation 20 ... 60 V
Rated Frequency (f) Auxilia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBK174237R1100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.