

## INDUSTRIAL COMPONENT DATA

# DS201MC40A300 2CSR275140R3404 ABB DS201 M C40 A300 RCBO

Brand: ABB | Manufacturer Part Number: DS201MC40A300



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | DS201MC40A300                 |
| Catalog number  | 2CSR275140R3404               |
| Category        | Earth leakage circuit breaker |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-79C33B7B5E                 |
| Generated       | 2026-07-29                    |

## Product Overview

DS201 M C40 A300 - RCBO

I.com.DS200M 1p+N C 40A 10kA 300mA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Tertiary / Industrial &gt; DS200

## Additional Product Information

The DS201 series RCBO is a 1P+N in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

## Ordering

EAN:8012542114055

Minimum Order Quantity:1 piece

Customs Tariff Number:85363030

## Dimensions

Product Net Width:0.035m

Product Net Height:0.085m

Product Net Depth:0.069m

Product Net Weight:0.239kg

## Container Information

Package Level 1 Units:5 piece

Package Level 1 Width:0.253 m  
Package Level 1 Height:0.088 m  
Package Level 1 Length:0.108 m  
Package Level 1 Gross Weight:1.446 kg  
Package Level 1 EAN:8012542114062

**Technical**  
Standards:IEC 61009-1  
IEC 61009-2-1  
EN 61009-1  
EN 61009-2-1  
Type of Residual Current:A type  
Rated Residual Current:300 mA  
Tripping Characteristic:C  
Rated Current (In):40 A  
Number of Poles:2  
Number of Protected Poles:1  
Rated Short-Circuit Capacity (Icn):(230 / 400 V AC) 10 kA  
Position of Neutral Terminals:Right  
Power Loss:8.6 W

**Environmental**  
RoHS Status:Following EU Directive 2002/95/EC August 18, 2005 and amendment  
Certificates and Declarations (Document Number)  
Declaration of Conformity - CE:2CSC421001D2702  
RoHS Information:2CSC422002K0201

**Classifications**  
Object Classification Code:Q  
ETIM 4:EC000905 - Earth leakage circuit breaker  
ETIM 5:EC000905 - Earth leakage circuit breaker

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / DS201MC40A300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.