

INDUSTRIAL COMPONENT DATA

2CSM204713R1801 ABB E 91/32 PV Fuse holder

Brand: ABB | Manufacturer Part Number: 2CSM204713R1801



Manufacturer	ABB
MPN / Reference	2CSM204713R1801
Catalog number	204713
Category	Holder for cylindrical fuse
Minimum order	1 Pcs
Document ID	EO-EFAED7E12E
Generated	2026-08-03

Product Overview

E 91/32 PV Fuse holder
 Fuse holder base E91/32PV 32A 1p
 E 91/32 PV Fuse disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Other modular devices > E90 E930 E9F
--------------	--

Additional Product Information

Technical
 Number of Protected Poles 1
 Number of Poles 1P
 Tightening Torque 2-2.5 N·m
 Utilization Category Connecting and disconnecting under no-load conditions - occasional actuation (DC-20B)
 Fuse Type gPV
 Lock Type Padlockable
 Sealing Type Sealing Wire
 Material of Conductor Copper
 Options Provided No
 Recommended Screw Driver Pozidriv 2
 Remarks For use with CU only 60°C, 75°C or 90°C wire
 Shock and Vibration Withstand acc. to IEC 61373 Category 1, Class B
 Connecting Capacity Stranded 1.5...16 mm²

Rigid 1.5...25 mm²
Fuse Size 10x38 mm
Operating Humidity (RHamb) max. 90% at +20 °C
50% at max. +40 °C
Electrical
Rated Voltage (Ur) 1000 V
Rated Operational Voltage DC-20B 1000 V DC
Rated Insulation Voltage (Ui) 1 kV
Rated Current (In) 32 A
Power Loss Total 3 W
at Rated Operating Conditions per Pole 3 W
Technical UL/CSA
Connecting Capacity UL/CSA Stranded 16...3 AWG
Rigid 16...10 AWG
Tightening Torque UL/CSA 18-22 in·lb
Material Compliance
RoHS Declaration 2CSC444003D2701
RoHS Information Following EU Directive 2011/65/EU
RoHS Date 20140101
REACH Declaration 9AKK108467A9482
REACH Information True - contains substances > 0.1 mass percentage
REACH Date 20240429
Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B Business To Consumer
Environmental
Ambient Air Temperature Operation -5...+40 °C
Storage -25...+70 °C
Degree of Protection IP20
Maximum Operating Altitude Permissible 2000 m
Resistance t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSM204713R1801 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.