

**INDUSTRIAL COMPONENT DATA**

## 2CSM204723R1801 ABB E 94/32 Fuse holder

Brand: ABB | Manufacturer Part Number: 2CSM204723R1801



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | ABB                         |
| MPN / Reference | 2CSM204723R1801             |
| Catalog number  | 204723                      |
| Category        | Holder for cylindrical fuse |
| Minimum order   | 1 Pcs                       |
| Document ID     | EO-09E1217E48               |
| Generated       | 2026-08-02                  |

### Product Overview

E 94/32 Fuse holder  
 Fuse holder base E94/32 32A 4p  
 E 94/32 Fuse switch disconnecter

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      ABB &gt; Other modular devices &gt; E90 E930 E9F

### Additional Product Information

Technical  
 Number of Protected Poles 4  
 Number of Poles 4P  
 Tightening Torque 2...2.5 N·m  
 Utilization Category Connecting and disconnecting under no-load conditions - occasional actuation (AC-20B)  
 Switching of mixed resistive and inductive loads, including moderate overloads - occasional actuation (AC-22B)  
 Lock Type Padlockable When Open  
 Sealing Type Sealing Wire  
 Material of Conductor Copper  
 Options Provided No  
 Recommended Screw Driver Pozidriv 2  
 Shock and Vibration Withstand acc. to IEC 61373 Category 1, Class B  
 Connecting Capacity Rigid 2x5 mm<sup>2</sup>  
 Stranded 2x2-5 mm<sup>2</sup>

Fuse Size 10x38 mm  
Operating Humidity (RHamb) max. 90% with temp. +20 °C  
50% with max. temp. +40 °C  
Rated Operational Current AC (Ie) 32 A  
Electrical  
Rated Voltage (Ur) acc. To IEC 400 V  
acc. To UL 690 V  
Rated Operational Voltage AC-20B 690 V  
AC-22B 400 V  
Rated Insulation Voltage (Ui) 1 kV  
Rated Frequency (f) 50/60 Hz  
Power Loss Total 12 W  
at Rated Operating Conditions per Pole 3 W  
Technical UL/CSA  
Connecting Capacity UL/CSA Rigid 2x10 AWG  
Stranded 2x14-10 AWG  
Material Compliance  
RoHS Declaration 9AKK106713A5623  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
RoHS Date 20140101  
REACH Declaration 9AKK108467A9482  
REACH Information True - contains substances > 0.1 mass percentage  
REACH Date 20240429  
Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363  
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)  
WEEE B2C / B2B Business To Consumer  
Environmental  
A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSM204723R1801 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.