

INDUSTRIAL COMPONENT DATA

1SAX111001R1103 ABB E16DU-2.7 Electronic Overload Relay

Brand: ABB | Manufacturer Part Number: 1SAX111001R1103



Manufacturer	ABB
MPN / Reference	1SAX111001R1103
Catalog number	111001
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-BD37588D99
Generated	2026-07-31

Product Overview

E16DU-2.7 Electronic Overload Relay

E16DU2,7 R.ELEC. 2.7A-No Eex Overload

E16DU-2.7 Electronic Overload Relay 0.80 ... 2.7 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Thermal Relays Classic Range

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Instructions and Manuals 2CDC107019M5502

Instructions and Manuals (Part 2) 1SAC200017M0002

Time-Current Characteristic Curve 1SAX100502F0002

1SAX100508F0001

CAD Dimensional Drawing 2CDC001079B0201

Dimension Diagram 1SAX100402F0001

1SAX100401F0001

Dimensions

Product Net Width 44.4 mm

Product Net Height 74.6 mm

Product Net Depth / Length 57 mm

Product Net Weight 0.15 kg

Technical

Setting Range 0.80 ... 2.7 A

Rated Operational Voltage Auxiliary Circuit 600 V AC/DC

Main Circuit 690 V AC

Rated Operational Current (Ie) 2.7 A

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Main Circuit 50 Hz

Main Circuit 60 Hz

Rated Impulse Withstand Voltage (Uimp) Auxiliary Circuit 6 kV

Main Circuit 6 kV

Rated Insulation Voltage (Ui) 690 V

Number of Poles 3

Number of Auxiliary Contacts NC 1

Number of Auxiliary Contacts NO 1

Number of Protected Poles 3

Conventional Free-air Thermal Current (Ith) Auxiliary Circuit NC 6 A

Auxiliary Circuit NO 6 A

Rated Operational Current AC-15 (Ie) (240 V) NC 3 A

(240 V) NO 3 A

(400 V) NC 1.1 A

(400 V) NO 1.1 A

(500 V) NC 0.72 A

(500 V) NO 0.72 A

Rated Operational Current DC-13 (Ie) (125 V) NC 0.55 A

(125 V) NO 0.5 A

(24 V) NC 1.5 A

(24 V) NO 1.5 A

(250 V) NC 0.27 A

(250 V) NO 0.27 A

(60 V) NC 0.55 A

(60 V) NO 0.55 A

Degree of Protection IP20

Pollution Degree 3

Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAX111001R1103 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.