

**INDUSTRIAL COMPONENT DATA**

# 2CCA703002R0001 ABB E211-32-10 Switch 32A 1NO 250VAC

Brand: ABB | Manufacturer Part Number: 2CCA703002R0001



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | ABB                                |
| MPN / Reference | 2CCA703002R0001                    |
| Catalog number  | 703002                             |
| Category        | Main switch for distribution board |
| Minimum order   | 10 Pcs                             |
| Document ID     | EO-59AFD0DBD5                      |
| Generated       | 2026-07-29                         |

## Product Overview

E211-32-10 Switch 32A 1NO 250VAC

Int.de remote E211-32-10 32A 1NA

ON-OFF Switch, 32 A, acc. to EN 250/400 V AC, 1NO, El. Color: Grey, MW: 0.5

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB &gt; Other modular devices &gt; E210

## Additional Product Information

Technical

Rated Service Short-Circuit Breaking Capacity (Ics) 3 kA

Contact Position Indication ON / OFF

Number of Main Contacts NC 0

Number of Main Contacts NO 1

Number of Poles 1P

Tightening Torque 1.2-1.5 N·m

Utilization Category Switching of mixed resistive and inductive loads, including moderate overloads - frequent actuation (AC-22A)

Switching of mixed resistive and inductive loads, including moderate overloads (i.e. shunt motors) - frequent actuation (DC-22A)

Switch Type Double Interrupting Contacts

Material of Conductor Copper

Remarks Sealable in the On and Off positions

Cover Color Grey  
Connecting Capacity Solid 1x1...6 mm<sup>2</sup>  
Solid 2x2.5 mm<sup>2</sup>  
Flexible 1x0.75...2x2.5 mm<sup>2</sup>  
Rated Operational Current AC-22A (I<sub>e</sub>) (400 V) 32 A  
Rated Operational Current DC-22A (I<sub>e</sub>) (50 V DC) 32 A  
(200 V DC) 3 A  
Electrical  
Short-Circuit Current Rating (SCCR) 3 kA  
Rated Voltage (U<sub>r</sub>) Minimum 250 V  
Rated Operational Voltage acc. to EN 250/400 V AC  
acc. to UL 508 240 V AC  
Rated Impulse Withstand Voltage (U<sub>imp</sub>) 6 kV  
Input Voltage Type AC  
Rated Current (I<sub>n</sub>) 32 A  
Rated Frequency (f) 50/60 Hz  
Minimum Switching Capacity 24 V AC  
25 mA  
Power Loss Total 1.12 W  
Number of Contacts NO 1  
Number of Auxiliary Contacts CO (SPDT) 0  
Design  
Control Element Color Grey  
Material Compliance  
RoHS Declaration 2CCC441013D0201  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
RoHS Date 20170426  
REACH Declaration 2CCC005047D0201  
REACH Information False - does not contain substances > 0.1 mass...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCA703002R0001 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.