

INDUSTRIAL COMPONENT DATA

2CCA703161R0001 ABB E217-16-10 C Illuminated push button red 16A 1NO 250VAC LED 115 ... 250VAC

Brand: ABB | Manufacturer Part Number: 2CCA703161R0001



Manufacturer	ABB
MPN / Reference	2CCA703161R0001
Catalog number	703161
Category	Push button for distribution board
Minimum order	10 Pcs
Document ID	EO-0C99D3429E
Generated	2026-08-03

Product Overview

E217-16-10 C Illuminated push button red 16A 1NO 250VAC LED 115 ... 250VAC

Lum pushbutton. E217-16-10C 16A Red 1NA

Luminous Pushbutton, 16 A, acc. to EN 250 V AC, 1NO, El. Color: Grey, 1LED, Red, MW: 0.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Other modular devices > E210

Additional Product Information

Technical

Maximum Switching Voltage 250 V

Number of Main Contacts NC 0

Number of Main Contacts NO 1

Number of Poles 1P

Number of LEDs 1

Tightening Torque 1.2-1.5 N·m

Switch Type Double Interrupting Contacts

Material of Conductor Copper

Remarks Sealable in the On and Off positions

Lamp Color Red

Connecting Capacity Solid 1x1...6 mm²

Solid 2x2.5 mm²

Flexible 1x0.75...2x2.5 mm²

Electrical

Rated Voltage (Ur) Lamp 230 ... 250 V

Rated Operational Voltage acc. to EN 250 V AC

acc. to UL 508 240 V AC

Voltage Range 115 ... 250 V AC

Auxiliary Voltage AC/DC LED Indicator 115...250 V AC

Rated Current (In) 16 A

Rated Frequency (f) 50/60 Hz

Power Loss 1.1 W

Power Watt 1.1 W

Number of Contacts NO 1

Number of Auxiliary Contacts CO (SPDT) 0

Design

Color Red

Control Element Color Grey

Material Compliance

RoHS Declaration 2CCC441014D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Date 20170426

REACH Declaration 2CCC005047D0201

REACH Information False - does not contain substances > 0.1 mass percentage

REACH Date 20190425

Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363

WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B Business To Consumer

Environmental

Ambient Air Temperature Operation -25...+55 °C

Storage -40...+70 °C

Degree of Protection IP20

Environmental Information 2CCC441003C0201

Dimensions

Width in Number of Modular Spacings 0.5

Product Net Width 9 mm

Product Net Height 85 mm

Product Net Depth....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCA703161R0001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.