


INDUSTRIAL COMPONENT DATA

2CCA703910R0001 ABB E219-91-10C2CD Indicator light with 2 LEDs green, red 115-230VAC

Brand: ABB | Manufacturer Part Number: 2CCA703910R0001



Manufacturer	ABB
MPN / Reference	2CCA703910R0001
Catalog number	703910
Category	Indicator light for distribution board
Minimum order	10 Pcs
Document ID	EO-FE57F13D24
Generated	2026-08-02

Product Overview

E219-91-10C2CD Indicator light with 2 LEDs green, red 115-230VAC

Green+red pilot E219-2CD 115-230Vac

Indicator Light, 16 A, 115 ... 230 V AC, 2LED, Red / Green, MW: 0.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Other modular devices > E210
--------------	------------------------------------

Additional Product Information

Technical

Number of LEDs 2

Tightening Torque 1.2-1.5 N·m

Lamp Type LED

Switch Type Double Interrupting Contacts

Material of Conductor Copper

Remarks Sealable in the On and Off positions

Lamp Color Red / Green

Connecting Capacity Solid 1x1...6 mm²

Solid 2x2.5 mm²

Flexible 1x0.75...2x2.5 mm²

Service Life LED Indicator 50000 hour

Electrical

Short-Circuit Current Rating (SCCR) 3 kA
Rated Voltage (Ur) 230 V
Rated Operational Voltage 115 ... 230 V AC
Rated Insulation Voltage (Ui) 250 V
Voltage Range 115 ... 250 V AC
Rated Impulse Withstand Voltage (Uimp) 4 kV
Auxiliary Voltage AC/DC LED Indicator 115...250 V AC
Input Voltage Type AC
Rated Current (In) 16 A
Rated Frequency (f) 50/60 Hz
Power Loss Total 0.47-1 W
Power Watt 0.8 W
Design
Color Green, red
Material Compliance
RoHS Declaration 2CCC441015D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date 20170426
REACH Declaration 2CCC005047D0201
REACH Information False - does not contain substances > 0.1 mass percentage
REACH Date 20190425
Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B Business To Consumer
Environmental
Ambient Air Temperature Operation -25...+55 °C
Storage -40...+70 °C
Environmental Information 2CCC441002C0201
Dimensions
Width in Number of Modular Spacings 0.5
Product Net Width 9 mm
Product Net Height 85 mm
Product Net Depth / Length 68 mm
Product Net Weight 45 g
Built-In....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCA703910R0001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.