

INDUSTRIAL COMPONENT DATA

1SDA059306R1 ABB E2S 1000 PR121/P-LSI In 1000A 3p W MP

Brand: ABB | Manufacturer Part Number: 1SDA059306R1



Manufacturer	ABB
MPN / Reference	1SDA059306R1
Catalog number	059306
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-64E8DC93D5
Generated	2026-08-01

Product Overview

E2S 1000 PR121/P-LSI In=1000A 3p W MP
E2S1000 PR121/P LSI 3P W MP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Service Breakers
--------------	------------------------

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) Document availability on demand
Environmental
Environmental Information 9AKK10103A6076
REACH Declaration 9AKK108466A1425
RoHS Information 9AKK108466A1424
RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Ordering
EAN 8015644616670
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions
Product Net Width 324 mm
Product Net Height 461 mm
Product Net Depth / Length 396.5 mm

Product Net Weight 49 kg
Container Information
Package Level 1 Units 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 600 mm
Package Level 1 Depth / Length 515 mm
Package Level 1 Gross Weight 59 kg
Package Level 1 EAN 8015644609139
Additional Information
Current Type AC
Electrical Durability $U_e \leq 440 \text{ V } 15000 \text{ cycle}$
 $U_e = 500 \dots 690 \text{ V } 15000 \text{ cycle}$
30 cycles per hour
Mechanical Durability 25000 cycle
60 cycles per hour
Number of Poles 3
Power Loss 83.2 W
Product Main Type SACE Emax
Product Name Air Circuit Breaker
Product Type Air Circuit Breaker
Rated Current (I_n) 1000 A
Rated Voltage (U_r) 690 V
Rated Impulse Withstand Voltage (U_{imp}) 12 kV
Rated Insulation Voltage (U_i) 1000 V
Rated Operational Current (I_e) 1000 A
Rated Operational Voltage 690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}) (220 V AC) 85 kA
(230 V AC) 85 kA
(380 V AC) 85 kA
(400 V AC) 85 kA
(415 V AC) 85 kA
(440 V AC) 85 kA
(500 V AC) 65 kA
(660 V AC) 65 kA
(690 V AC) 65 kA
Rated Short-time Withstand Current Low Volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA059306R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.