INDUSTRIAL COMPONENT DATA

1SDA058285R1 ABB E2S 800 PR122/P-LI In 800A 3p F HR

Brand: ABB | Manufacturer Part Number: 1SDA058285R1

Manufacturer	ABB
MPN / Reference	1SDA058285R1
Catalog number	058285
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-38DD65B311
Generated	2026-08-04

Product Overview

E2S 800 PR122/P-LI In=800A 3p F HR
E2S800 PR122/P LI 3P F HR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Service Breakers

Additional Product Information

Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) Document availability on demand
Environmental
Environmental Information 9AKK10103A6076
Ordering
EAN 8015644605735
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions
Product Net Width 296 mm
Product Net Height 418 mm
Product Net Depth / Length 302 mm

Product Net Weight 45 kg
Container Information
Package Level 1 Units 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 600 mm
Package Level 1 Depth / Length 515 mm
Package Level 1 Gross Weight 55 kg
Package Level 1 EAN 8015644605735
Additional Information
Product Main Type SACE Emax
Product Name Air Circuit Breaker
Product Type Air Circuit Breaker
Version F
Technical
Current Type AC
Electrical Durability Ue =< 440 V 15000 cycle
Ue = 500 ... 690 V 15000 cycle
30 cycles per hour
Mechanical Durability 25000 cycle
60 cycles per hour
Number of Poles 3P
Power Loss 29 W
Rated Current (In) 800 A
Rated Impulse Withstand Voltage (Uimp) 12 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Current (Ie) 800 A
Rated Operational Voltage 690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics) (220 V AC) 85 kA
(230 V AC) 85 kA
(380 V AC) 85 kA
(400 V AC) 85 kA
(415 V AC) 85 kA
(440 V AC) 85 kA
(500 V AC) 65 kA
(660 V AC) 65 kA
(690 V AC) 65 kA
Rated Short-time Withstand Current Low Volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA058285R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.