

INDUSTRIAL COMPONENT DATA

1SDA073918R1 ABB E6.2 W FP Iu 5000 4p HR HR

Brand: ABB | Manufacturer Part Number: 1SDA073918R1



Manufacturer	ABB
MPN / Reference	1SDA073918R1
Catalog number	073918
Category	Chassis part power circuit breaker
Minimum order	1 Pcs
Document ID	EO-1635222BEC
Generated	2026-07-31

Product Overview

E6.2 W FP Iu=5000 4p HR HR

FIXED BASE W TER. HR-HR 4P Iu5000 -E6.2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Rack "Megamax-Emax" > E6.2

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK108467A6707

Ordering

Order Code US and Canada ZDC50A0XX

EAN 8015644778514

Minimum Order Quantity 1 piece

Customs Tariff Number 85389099

Dimensions

Product Net Width 929 mm

Product Net Height 425 mm

Product Net Depth / Length 383 mm

Product Net Weight 100 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 570 mm

Package Level 1 Height 610 mm

Package Level 1 Depth / Length 1127 mm

Package Level 1 Gross Weight 109 kg

Package Level 1 EAN 8015644778514

Additional Information

Product Main Type SACE Emax 2

Product Name Fixed Part

Product Type Fixed Part

Version W FP

Technical

Connecting Capacity 5000 mm²

Current Type AC

Neutral Pole Current ([%I_n]) 50 %

Number of Poles 4P

Rated Current (I_n) 5000 A

Rated Impulse Withstand Voltage (U_{imp}) acc. to IEC 60947-2 12 kV

Rated Insulation Voltage (U_i) AC 1000 V

Rated Operational Voltage 690 V AC

800 V AC

900 V AC

Rated Uninterrupted Current (I_u) 5000 A

Rated Voltage (U_r) 900 V

Recommended Screw Driver M12

Standards IEC

Sub-type E6.2

Terminal Connection Type Rear flat Horizontal

Terminal Type Bolt

Tightening Torque 70 N·m

Certificates and Declarations

ATEX Certificate No c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA073918R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.