

INDUSTRIAL COMPONENT DATA

1SAX531001R1101 ABB EF205-210 Electronic Overload Relay

Brand: ABB | Manufacturer Part Number: 1SAX531001R1101



Manufacturer	ABB
MPN / Reference	1SAX531001R1101
Catalog number	531001
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-55B8CABE9D
Generated	2026-07-31

Product Overview

EF205-210 Electronic Overload Relay
EF205-210 ELECTRONIC OVERLOAD RELAY
EF205-210 Electronic Overload Relay 63 ... 210 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Contactors and overload relays > Electronic Overload**

Additional Product Information

Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85364900
Popular Downloads
Data Sheet, Technical Information 2CDC107042D0201
Instructions and Manuals 2CDC107036M6803
Instructions and Manuals (Part 2) 1SAC200017M0002
Ex Operating Instructions 2CDC107043M6801
Time-Current Characteristic Curve 1SAX100509F0002
1SAX100510F0001
CAD Dimensional Drawing 2CDC001079B0201
Dimension Diagram 1SAX500401F0001
Dimensions
Product Net Width 105 mm

Product Net Height 171 mm

Product Net Depth / Length 122.8 mm

Product Net Weight 1.256 kg

Technical

Setting Range 63 ... 210 A

Rated Operational Voltage Auxiliary Circuit 600 V AC/DC

Main Circuit 1000 V AC

Rated Operational Current (Ie) 210 A

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Main Circuit 50 Hz

Main Circuit 60 Hz

Rated Impulse Withstand Voltage (Uimp) Auxiliary Circuit 6 kV

Main Circuit 8 kV

Rated Insulation Voltage (Ui) 1000 V

Number of Poles 3

Number of Auxiliary Contacts NC 1

Number of Auxiliary Contacts NO 1

Number of Protected Poles 3

Conventional Free-air Thermal Current (Ith) Auxiliary Circuit NC 5 A

Auxiliary Circuit NO 5 A

Rated Operational Current AC-15 (Ie) (240 V) NC 3 A

(240 V) NO 3 A

(400 V) NC 1.1 A

(400 V) NO 1.1 A

(500 V) NC 0.75 A

(500 V) NO 0.75 A

Rated Operational Current DC-13 (Ie) (125 V) NC 0.55 A

(125 V) NO 0.5 A

(24 V) NC 1.5 A

(24 V) NO 1.5 A

(250 V) NC 0.27 A

(250 V) NO 0.27 A

(60 V) NC 0.55 A

(60 V) NO 0.55 A

Degree of Protection Housing IP20

Main Circui...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAX531001R1101 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.