

INDUSTRIAL COMPONENT DATA

1SAX331001R1101 ABB EF65-70 Electronic Overload Relay

Brand: ABB | Manufacturer Part Number: 1SAX331001R1101



Manufacturer	ABB
MPN / Reference	1SAX331001R1101
Catalog number	331001
Category	Electronic overload relay
Minimum order	1 Pcs
Document ID	EO-4DE31F784B
Generated	2026-08-02

Product Overview

EF65-70 Electronic Overload Relay
EF65-70 ELECTRON RELAY. OVERLOAD 25-70A
EF65-70 Electronic Overload Relay 25 ... 70 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Contactors and overload relays > Electronic Overload**

Additional Product Information

Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85364900
Popular Downloads
Data Sheet, Technical Information 2CDC107041D0201
Instructions and Manuals 2CDC107026M6803
Instructions and Manuals (Part 2) 1SAC200017M0002
Ex Operating Instructions 2CDC107043M6801
Time-Current Characteristic Curve 1SAX100509F0002
1SAX100510F0001
CAD Dimensional Drawing 2CDC001079B0201
Dimension Diagram 1SAX300405F0001
Dimensions
Product Net Width 70 mm

Product Net Height 131.2 mm

Product Net Depth / Length 105.2 mm

Product Net Weight 0.821 kg

Technical

Setting Range 25 ... 70 A

Rated Operational Voltage Auxiliary Circuit 600 V AC/DC

Main Circuit 1000 V AC

Rated Operational Current (Ie) 70 A

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Main Circuit 50 Hz

Main Circuit 60 Hz

Rated Impulse Withstand Voltage (Uimp) Auxiliary Circuit 6 kV

Main Circuit 8 kV

Rated Insulation Voltage (Ui) 1000 V

Number of Poles 3P

Number of Auxiliary Contacts NC 1

Number of Auxiliary Contacts NO 1

Number of Protected Poles 3

Conventional Free-air Thermal Current (Ith) Auxiliary Circuit NC 6 A

Auxiliary Circuit NO 6 A

Rated Operational Current AC-15 (Ie) (240 V) NC 3 A

(240 V) NO 3 A

(400 V) NC 1.1 A

(400 V) NO 1.1 A

(500 V) NC 0.75 A

(500 V) NO 0.75 A

Rated Operational Current DC-13 (Ie) (125 V) NC 0.55 A

(125 V) NO 0.5 A

(24 V) NC 1.5 A

(24 V) NO 1.5 A

(250 V) NC 0.27 A

(250 V) NO 0.27 A

(60 V) NC 0.55 A

(60 V) NO 0.55 A

Degree of Protection Housing IP20

Main Circui...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAX331001R1101 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.