

**INDUSTRIAL COMPONENT DATA**

# 1SFA619552R1051 ABB EMERGENCY STOP CE4K1-10R-02

Brand: ABB | Manufacturer Part Number: 1SFA619552R1051



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | ABB                     |
| MPN / Reference | 1SFA619552R1051         |
| Catalog number  | 619552                  |
| Category        | Emergency stop complete |
| Minimum order   | 1 Pcs                   |
| Document ID     | EO-5AB71EA4E3           |
| Generated       | 2026-08-04              |

## Product Overview

EMERGENCY STOP#CE4K1-10R-02  
EMERGENCY MUSHROOM CE4K1-10R-02  
CE4K1-10R-02 Emergency stop

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                            |
|--------------|--------------------------------------------|
| Catalog path | ABB > Command and signaling > elements PDA |
|--------------|--------------------------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece  
Customs Tariff Number 8536508000

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_  
Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 0.04 m  
Product Net Height 0.04 m  
Product Net Depth / Length 0.103 m  
Product Net Weight 0.068 kg

**Technical**

Ambient Air Temperature Operation -25 ... +70 °C  
Storage -40 ... +85 °C

Color Red  
Actuator Type Mushroom 40 mm  
Illumination Non-illuminated  
Function Maintained  
Sub-Function Key release  
Key Code Key code 71  
Number of Auxiliary Contacts NC 2  
Number of Auxiliary Contacts NO 0  
Enclosure Type NEMA Type1  
Type12  
Type13  
Type3R  
Type4  
Type4X  
Pollution Degree 3  
Rated Insulation Voltage (Ui) 300 V  
Rated Impulse Withstand Voltage (Uimp) 6 kV  
Rated Frequency (f) 50 / 60 Hz  
Rated Operational Voltage 24 ... 300 V  
Rated Operational Current DC-13 (Ie) (24 V) 0.3 A  
(125 V) 0.2 A  
Rated Operational Current AC-15 (Ie) (240 V) 2 A  
(220 / 240 V) 2 A  
Power Loss Maximum 5 W  
Mechanical Durability 50000 cycle  
Connecting Capacity Flexible with Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible 1 x 0.5 ...1.5 mm<sup>2</sup>  
Flexible 2 x 0.5 ...1.5 mm<sup>2</sup>  
Solid 1 x 0.5...1.5 mm<sup>2</sup>  
Solid 2 x 0.5...1.5 mm<sup>2</sup>  
Connection Type Screw Clamp  
Terminal Type Screw Terminals  
Tightening Torque 0.8 N·m  
Wire Stripping Length 6 mm  
Technical UL/CSA  
Connecting Capacity UL/CSA 1x 22...14 AWG  
2x 22...14 AWG  
E...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619552R1051 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.