

INDUSTRIAL COMPONENT DATA

2CSF202001R4630 ABB F202 AC-63/0,5 Residual Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF202001R4630



Manufacturer	ABB
MPN / Reference	2CSF202001R4630
Catalog number	202001
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-1EA063C0A6
Generated	2026-07-31

Product Overview

F202 AC-63/0,5 Residual Current Dev.
Int.dif.F202AC-63/0.5 2p 63A AC 500mA
Residual Current Circuit Breaker F200 - 2P - 500 mA - 63 A - Type AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial > F200AC

Additional Product Information

ABB EcoSolutions
ABB EcoSolutions Yes
EcoSolutions Profile 9AKK108469A3794
Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 82.05 %
ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill
UL 2799 Zero Waste To Landfill Validation available
Sustainable Material Content in Packaging (wt. %) Recycled Paper - 0 %
Recycled Paper - 3.91 %
Recycled Cardboard - 29.08 %
Recycled Cardboard - 61.23 %
Recycled Cardboard - 2.66 %
Extended Product Lifetime Product Durability
Offered with Takeback Services Take Back for Recycling
End Of Life Disassembling Instructions 9AKK108470A1748

Environmental Product Declaration - EPD 9AKK108469A9642

Technical

Type of Residual Current Type AC

Test Voltage (Ut) 110-254 V

Maximum Surge Current 0.25 kA

Leakage Current Type AC

Power Supply Connection Arbitrary

Electrical Endurance 10000 cycle

Mechanical Endurance 20000 cycle

Number of Poles 2P

Number of Modular Spacings per DIN Rail 2

Operating Characteristic Instantaneous

Tightening Torque 2.8 N·m

Accessory Type Auxiliary contact

Auxiliary/Signal contact

Shunt trip

Undervoltage release

Overvoltage release

Motor Operating Device

Bottom fitting auxiliary contact

Autoreclosing Unit

Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal

Cage Terminal

Failsafe Biconnect Fork Top/Bottom

Failsafe Biconnect Fork Bottom

Options Provided None

Accessories Available Yes

Connecting Capacity Busbar 10 mm²

Rigid 25....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF202001R4630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.