

**INDUSTRIAL COMPONENT DATA**

# 2CSF204401R1630 ABB F204 A-63/0,03 AP-R Res. Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF204401R1630



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | ABB                                     |
| MPN / Reference | 2CSF204401R1630                         |
| Catalog number  | 204401                                  |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-5DFEBC3762                           |
| Generated       | 2026-08-03                              |

## Product Overview

F204 A-63/0,03 AP-R Res. Current Dev.

I.dif.F204A-63/0.03APR 4p 63A A APR 30mA

Residual Current Circuit Breaker F200 - 4P - 30 mA - 63 A - Type A APR

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                          |
|--------------|------------------------------------------|
| Catalog path | ABB > Tertiary / Industrial > F200 (APR) |
|--------------|------------------------------------------|

## Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3794

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 82.05 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Paper - 0 %

Recycled Paper - 3.91 %

Recycled Cardboard - 29.08 %

Recycled Cardboard - 61.23 %

Recycled Cardboard - 2.66 %

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108470A1748  
Environmental Product Declaration - EPD 9AKK108469A9642  
Technical  
Type of Residual Current Type A APR  
Test Voltage (Ut) 170-254 V  
Maximum Surge Current 3 kA  
Leakage Current Type A  
Power Supply Connection Arbitrary  
Electrical Endurance 10000 cycle  
Mechanical Endurance 20000 cycle  
Number of Poles 4P  
Number of Modular Spacings per DIN Rail 4  
Operating Characteristic 10ms Delay (High Immunity)  
Position of Neutral Terminals Right  
Tightening Torque 2.8 N·m  
Accessory Type Auxiliary contact  
Auxiliary/Signal contact  
Shunt trip  
Undervoltage release  
Overvoltage release  
Motor Operating Device  
Bottom fitting auxiliary contact  
Autoreclosing Unit  
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal  
Cage Terminal  
Failsafe Biconnect Fork Top/Bottom  
Failsafe Biconnect Fork Bottom  
Options Provided None  
Accessories Available...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF204401R1630 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.