

## INDUSTRIAL COMPONENT DATA

## 2CSF204001R4630 ABB F204 AC-63/0,5 Residual Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF204001R4630



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | ABB                                     |
| MPN / Reference | 2CSF204001R4630                         |
| Catalog number  | 204001                                  |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-5DA9514087                           |
| Generated       | 2026-08-03                              |

## Product Overview

F204 AC-63/0,5 Residual Current Dev.

Int.dif.F204AC-63/0.5 4p 63A AC 500mA

Residual Current Circuit Breaker F200 - 4P - Type AC - 500 mA - 63 A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Tertiary / Industrial &gt; F200AC

## Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3794

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 82.05 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Paper - 00 %

Recycled Paper - 04 %

Recycled Cardboard - 29 %

Recycled Cardboard - 61 %

Recycled Cardboard - 03 %

Extended Product Lifetime Product Durability

End Of Life Disassembling Instructions 9AKK108470A1748

Environmental Product Declaration - EPD 9AKK108469A9642

**Technical**

Type of Residual Current Type AC  
Test Voltage (Ut) 110-254 V  
Maximum Surge Current 0.25 kA  
Leakage Current Type AC  
Power Supply Connection Arbitrary  
Electrical Endurance 10000 cycle  
Mechanical Endurance 20000 cycle  
Number of Poles 4P  
Number of Modular Spacings per DIN Rail 4  
Operating Characteristic Instantaneous  
Position of Neutral Terminals Right  
Tightening Torque 2.8 N·m  
Accessory Type Auxiliary contact  
Auxiliary/Signal contact  
Shunt trip  
Undervoltage release  
Overvoltage release  
Motor Operating Device  
Bottom fitting auxiliary contact  
Autoreclosing Unit  
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal  
Cage Terminal  
Failsafe Biconnect Fork Top/Bottom  
Failsafe Biconnect Fork Bottom  
Options Provided None  
Accessories Available Yes  
Connecting Capacity Busbar 10 mm<sup>2</sup>  
Rigid 25 ... 25 mm<sup>2</sup>  
Flexible 25 ... 2...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / 2CSF204001R4630 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.