

INDUSTRIAL COMPONENT DATA

2CCF544110E0630 ABB F404A63/0.03 3PN,63A,30mA SMISSLINE

Brand: ABB | Manufacturer Part Number: 2CCF544110E0630



Manufacturer	ABB
MPN / Reference	2CCF544110E0630
Catalog number	544110
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-C0C35FCE09
Generated	2026-08-04

Product Overview

F404A63/0.03 3PN,63A,30mA SMISSLINE

SMISSLINE-I. Diff.F404A63/0.03

Smisline F400 Differential Switch - 4P - 30 mA - 63 A - Type A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial > SMISSLINE

Additional Product Information

F404A63/0.03 3PN,63A,30mA SMISSLINE

Ordering

EAN:7612270104291

Minimum Order Quantity:1 piece

Customs Tariff Number:85363020

Dimensions

Product Net Width:91mm

Product Net Height:97mm

Product Net Length:72 mm

Product Net Depth:72mm

Product Net Weight:0.43kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:101 mm
Package Level 1 Height:89 mm
Package Level 1 Length:76 mm
Package Level 1 Gross Weight:0.49 kg
Package Level 1 EAN:7612270104291
Environmental
RoHS Status:Following EU Directive 2002/95/EC August 18, 2005 and amendment
Additional Information
IIT Publishing Status:Level 0 - Information enabled
Power Loss:4.4 W
Product Main Type:F404
Product Name:F404
Rated Operational Current (Ie):63 A
Rated Operational Voltage:230 / 400 V AC
Rated Residual Current:0.03_AMPx
Rated Voltage (Ur):230 / 400 V
Standards:EN 61008-1
Certificates and Declarations (Document Number)
Data Sheet, Technical Information:2CCC451059C0202
Declaration of Conformity - CE:2CCY451110D0601
RoHS Information:2CCC451021D0201
Classifications
ETIM 4:EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:EC002297 - Residual current circuit breaker (RCCB) module
Object Classification Code:FB
ETIM for 2CCF544110E0630 Circuit breakers and fuses (EC000003)
Feature Name
Feature Value
Number of poles (EF001391)
4
Rated voltage (EF000228)
400 V
Rated current (EF000227)
63 A
Rated fault current (EF002358)
0.03 A
Rated insulation voltage Ui (EF001366)
500 V
Rated impulse withstand voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCF544110E0630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.